


Intake Kit Installation Instructions: 1999.5-2003 Ford F-Series Super Duty/Excursion V8-7.3L (td)

Step 8

POWER	<u>Kit Part #:</u>	Kit Part #: 51-10061-1		Tools Required	Part Lis	Part List	
	54-10061-1			5/16 nut driver or socket	1	Air Filter Replacement P/N (24-40035	
	75-10061-1			Flathead screwdriver		Pro GUARD 7 72-40035 or Pro Dry S 21-40035)	
	Make:	Make: Ford			1	Air filter housing	
	Model:	Year:	Engine:		1	Housing splash guard	
	F-250	'99.5-'03	V8-7.3L (td)		4	#8-32 Phillips screws	
advanced FLOW engineering™ P.O. Box 1719	F-350	'99.5-'03	V8-7.3L (td)		1	#006 Hose clamp	
	F-450	'00-'03	V8-7.3L (td)		1	1.5" X 1/2" Hose	
Corona, CA 92878	F-550	'01-'03	V8-7.3L (td)		1	Trim seal 3/4" (35")	
Support: 951-493-7100	Excursion	'00-'03	V8-7.3L (td)				
aFepower.com							



Complete kit components



Complete Stock Intake. Disconnect battery before install.



Remove the upper portion of the air box by loosening the hose clamp on the air box. Carefully remove the air filter minder on the side of the air box.



Step 4

Loosen the air box lid clamps and remove air box lid and OEM air filter.



Your aFe intake installation is now complete. Make sure all clamps are tight and that all electrical components are secure. Check and tighten connections after a few hours of operation. Thank you for choosing aFepower!



Place the new air filter inside the new housing and tighten the clamp. Next attach the front splash guard to the front of the housing. Secure with the provided screws.

Place enclosed CARB EO sticker on a clean/smooth surface on or near the intake system. EO identification label is required in passing the Smog Check inspection.



Take kit and insert taps of splash panel into slots on the lower half of OE housing at an angle. (Tabs are to be inserted into and rest on the bottom edge of slots. Do not hook tabs over plastic.



Depress spring tab slightly and lower the filter housing down into OE housing until the spring tab snaps into place.

