

TOP Racer Spacer Installation Instructions


	Parts List:	Tools Required	18-314 ^{xx}	Part #
	1- Fastener	Hacksaw or tube cutter		
	ב- Rubber Backed Washer	File	Fits all 5-1/2" carburated flange	Application:
	ם- Flat Washer	Aasking tape	səssd OD *4r	
	ל- Spacer			
	ב- TOP Racer תאו Filter			
			Note: Please confirm Parts List and read all instruction steps	
			installation.	before proceeding with a




ing tape may be used to mark the stud. mark the location of the top cap on the center stud. A single wrap of mask-With the air cleaner in place and properly seated on the carburetor pan



er in place. Do not over tighten the top nut, the filter should compress until the filter stud (rubber down) and use the supplied fastener (or of choice) to hold the air cleanis flat and in contact with the carburetor pan. Place the rubber faced washer on the stud over spacer. Position the air cleaner on the stud and make sure the bottom lip Slip the cut spacer over the carburetor stud and place a standard flat washer on the




top of the air filter. If the stud is not long enough it should be replaced. Do not press down or At this point you should check that there is no less than ${\cal U}_{4}$ " of center stud protruding from the Place air cleaner on and make sure it is fully seated and resting on the lower carburetor pan.



Support: 877-512-8111 Corona, CA 92878

P.O. Box 1719



any sharp edges left on the spacer. tape mark down to the top of the carburetor and subtract $1 \ 1/16$ inch from this measurement. Cut the supplied spacer to the calculated length. Use a file to remove Lift off the air cleaner being careful not to cause the tape to slide. Measure from the

cap is in firm contact with the spacer.