

IMPORTANT

2011-UP FORD MUSTANG with 5.0L Engine.

The enclosed Centerforce pressure plate assembly is designed to be used on late model Ford 5.0L engines. Please note that the Original Equipment (O.E.) Ford factory flywheel may utilize EITHER SIX or NINE pressure plate bolts. If you are using an O.E. flywheel that has provisions for NINE pressure plate bolts, your new Centerforce pressure plate will only be using SIX of the flywheel bolt holes. Specific instructions as follows:

For O.E. flywheels with NINE pressure plate bolts: in order to properly mount the Centerforce pressure plate to your flywheel, you **MUST use the THREE stepped** dowel pins (disregard the three straight side dowel pins enclosed) and SIX special pressure plate bolts enclosed. Remove the factory straight dowel pins and replace with the 3 supplied stepped dowel pins (large end of the pin will press fit into the flywheel). Centerforce recommends a small amount of thread locking compound to be used on the enclosed pressure plate bolts – locate your pressure plate over the 3 stepped dowel pins, then using the pressure plate bolts, draw the pressure plate up evenly to the flywheel by turning each bolt 1/4 turn at a time in a crisscross pattern. Once the pressure plate is completely drawn to the flywheel, torque all SIX bolts: **48 to 50 ft/lbs.**

For O.E. flywheels with SIX pressure plate bolts: in order to properly mount the Centerforce pressure plate to your flywheel, you **MUST use the THREE straight side** dowel pins (disregard the three stepped dowel pins enclosed) and use the SIX special pressure plate bolts enclosed. Install dowel pins into the flywheel (either end will press fit into the flywheel). Centerforce recommends a small amount of thread locking compound to be used on the enclosed pressure plate bolts – locate your pressure plate over the 3 dowel pins, then using the pressure plate bolts, draw the pressure plate up evenly to the flywheel by turning each bolt 1/4 turn at a time in a crisscross pattern. Once the pressure plate is completely drawn to the flywheel, torque all SIX bolts: **48 to 50 ft/lbs.**

**For more information please contact our Tech Line at:
(800) 932-5882**



"NOTE" Centerforce tip sheets are for general reference only. Please refer to your owners manual for vehicle specifications.

IMPORTANT