# **INSTALLATION INSTRUCTIONS**

**▲** WARNING: DO NOT EXCEED PRODUCT RATING OR TOW VEHICLE LAMP LOAD RATING, WHICHEVER IS LOWER

## **APPLICATIONS**

Make	Model
Dodge	Dakota
Dodge	Ram 1500
Dodge	Ram 2500 / 3500 with factory 7-way

### WIRING LOCATION GUIDE

### **PICKUP TRUCKS (T)**

Representative vehicle shown below

- T3 Behind driver side rear bumper
- T5 Behind passenger side rear bumper

### **CUSTOM WIRING HARNESS**





### NOTICE © (1)

All steps must be followed to ensure the wiring harness will function properly. Once installed, test for proper function by using a test light or connecting a properly wired trailer.

### **TOOLS NEEDED**

None



Exceeding the product rating can cause loss of warranty, overheating and potential fire. Do not exceed product rating or tow vehicle lamp load rating, whichever is lower.

Check vehicle owner's manual or contact the vehicle manufacturer for more information.

### INSTALLATION / SAFETY INSTRUCTIONS I

#### Step 1

Locate the vehicle taillight wiring harness connectors. The connectors will be similar to those on the custom wiring harness. Separate the connectors from the taillight housing taking care not to damage the locking tabs (A).

#### Step 2

Insert the custom wiring harness end with yellow wire between the separated connectors. Make sure the connectors are fully inserted with locking tabs in place (B).

#### Step 3

Route the custom wiring harness end with the green wire to the passenger side behind the removed scuff panels. Repeat steps 1-2 on the passenger side using the harness end with the green wire.

#### Step 4

When in use, route the 4-flat to the center of the vehicle and out of the trunk. When not in use, roll up and store in a convenient, out of the way location inside the trunk. Secure any loose wires with the provided cable ties.

■ WARNING: Check for miscellaneous items that may be hidden behind or under any surface before drilling to avoid damage and / or personal injury.

#### Step 5

Reinstall all items removed during install. Install the provided 4-flat dust cover to help prevent corrosion.



