15410

FORD F-250 / F-350 SUPER DUTY

9/10/2012

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 17,000 LBS. TRAILER WEIGHT & 2,550 LBS. TONGUE WEIGHT. GROSS LOAD CAPACITY WHEN USED AS A WEIGHT DISTRIBUTION HITCH: 17,000 LBS. TRAILER WEIGHT & 2,550 LBS. TONGUE WEIGHT

DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

Parts List	
ITEM QTY PART NUMBER DESCRIPTION	
1 8 9_16-12 x 1 3/4 CARRIAGE BOLT	$\neg \forall \land \land \land$
2 8 CM-SP71 .250 x 1.50 x 2.00" 9/16" SQUARE H	
3 8 9_16-12 FLANGE NUT HEX FLANGE NUT	
ITEM QTY PART NUMBER DESCRIPTION 1 8 9_16-12 x 1 3/4 CARRIAGE BOLT 2 8 CM-SP71 .250 x 1.50 x 2.00" 9/16" SQUARE H 3 8 9_16-12 FLANGE NUT HEX FLANGE NUT TOOLS REQUIRED 13/16" WRENCH 7/8" SOCKET 12" EXTENSION SOCKET WRENCH TORQUE WRENCH Briver Side FRAME RAIL DRIVER SIDE DRIVER SIDE DRIVER SIDE PLATE	
ERONAL P	
EAT 9	
*	
HITCH WEIGHT: 68 LBS.	
INSTALL TIME	
PROFESSIONAL: 30 MINUTES	
NOVICE (DIY): <u>60</u> MINUTES	
INSTALL NOTES:	
- NO DRILLING REQUIRED	
	V

INSTALLATION STEPS

Note: To ease installation, removal of the spare tire is recommended.

- 1. Position the hitch against the frame, aligning the holes in the hitch with the holes in the frame. Take note of the fastener locations and lower the hitch.
- 2. Place a carriage bolt and spacer into each bolt location from inside the frame rail as shown.
- 3. Raise the hitch into position and secure it to the frame rails using hex flange nuts, as shown.
- 4. Torque all hardware to 150 lb-ft.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing LLC., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing LLC, may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.