



**Before returning this product  
to the store of purchase**

**Contact Dee Zee if you experience the following problems:**

- Missing Parts
- Installation Problems/Questions
- Warranty Questions

**1.800.779.2102**

Hours of operation: 8am - 5pm CST, Mon-Friday

Review complete warranty policy and register your product at:

**[www.deezee.com/warranty.php](http://www.deezee.com/warranty.php)**

# **INSTALLATION INSTRUCTIONS**

**SIDE BAR**

**94-01DODGE RAM PICKUP STANDARD CAB**

**PART# DZ 370211/DZ 370212/DZ 370213**

---

**Step One:** Locate hardware and check contents with the hardware listed below.

QTY	DESCRIPTION
4	12 x 50mm Hex bolt, zinc plated
8	12mm Flat washer, zinc plated
8	12mm Split lock washer, zinc plated
4	10mm x 25mm Hex bolt
8	10mm Flat washer, zinc plated
4	10mm Hex nut, zinc plated
4	10mm Split lock washer, zinc plated
4	12mm x 1.75 x 110mm Hex head bolt, zinc plated
2	Front mounting bracket-small
2	Rear mounting bracket-large
2	Rear support bracket
4	3" Plastic rings

(Note: Passenger Side Tube is packed in the pink sleeve and Driver Side Tube is packed in clear sleeve)

**Step Two:** Remove the front and rear body mount bolts. There are a total of four mounting brackets in the hardware kit. Locate the two smaller brackets and loosely install them to the front body mount locations with the 12mm bolts and 12mm flat and lock washers. Repeat this process for the rear body mounts.

**Step Three:** Attach the side bars to the mounting brackets with the remaining 12mm hardware. Align and level the side bars and brackets at this time.

**Step Four:** Attach the support brackets to the rear attachment brackets with the 10mm hardware enclosed using the holes in the brackets that are towards the front of the vehicle.

**Step Five:** Using the remaining hole in the support bracket as a guide, mark and drill the body mount housing with a 7/16" drill and secure with the remaining 10mm hardware.

### Cleaning Instructions

Dual-Stage Hi-gloss Gloss Black Powder Coat. Mild soap, window or glass cleaner may be used. Do not use any type of polish or wax that contains abrasives that could damage the finish.

Stainless Steel finish: Mild soap, window or glass cleaner may be used. Aluminum polish may be used to polish small scratches and scuffs on the finish.