

M-6687-A351 Windage Tray INSTRUCTION SHEET

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD RACING PERFORMANCE PARTS

Please contact the Tech Line for the most current instruction information (800) 367-3788

!!! PLEASE READ THE FOLLOWING INSTRUCTIONS CAREFULLY PRIOR TO INSTALLATION!!!

INSTALLATION INSTRUCTIONS:

The M-6687-A351 windage tray requires hand fitting to the engine assembly. The crankshaft scraper must be ground with a handheld die grinder to clear the crankshaft counterweights. A close fit is necessary to obtain maximum benefit from the windage tray. The following is a suggested procedure. (Note: This is not too difficult with the engine on an engine stand; if the engine is in a vehicle, it will be a little awkward.)

- **Step 1:** Remove the oil pan and oil pump pick-up tube.
- Step 2: Remove the number 2 and number 4 main cap bolts and replace with the four special fasteners supplied with the windage tray. Torque the bolts to 105 ft./lbs.
- **Step 3:** Paint the windage tray scraper with Machinist Blue or a similar marking compound.
- Step 4: Set the tray in place on the studs. The slotted holes will allow the tray to slide sideways to clear the crankshaft. Hold the tray against the crank with light pressure as you turn the crank. This will leave witness marks in the Machinist Blue. Grind the marked areas and refit the tray. Repeat the process until the scraper has .050"in clearance to the crank and rods with the tray centered over the crank. Hand tighten the nuts provided.
- **Step 5:** Trial fit the oil pan to insure it clears the windage tray. If it does not clear, repeat step 4 removing additional material from the scraper.
- **Step 6:** Material may also have to be ground around the slotted holes for socket clearance.
- Step 7: After all clearancing is completed, smooth all edges. Reinstall the oil pump pick-up screen and tube assembly. Tighten windage tray nuts. Reinstall oil pan.

Tech Line (800) 367-3788

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356