

If you have any comments or concerns,
 please feel free to contact our
 customer service department at:
 Toll-free: 1-800-835-0438
 OR
 Email: info@gofia.com

SEAT COVERS
 BY



FEATURING

SUPER-GRIP®

THE SLIP RESISTANT FASTENING SYSTEM

INSTALLATION INSTRUCTIONS
 FOR
 Oe32-16, TR42-16, SP82-16

Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

INSTRUCTIONS:

A) CUSHION COVERS:

1. Remove seat belt buckles from holder on cushion
2. Center cover on seat
3. Slip seat belt buckles through elastics on seat covers
4. Lift cushion halfway to up position







5. Insert strap through crevice and buckle
6. Attach velcro to carpet on underside of cushion
7. Adjust all straps, buckles and velcro to equalize tension

B) BACKREST COVER:

1. Remove headrests (see NOTE 2)
2. Slip cover over backrest. Ensure cover is installed under seat belt
3. Pass top straps behind the seat so they go to floor (see NOTE 3)
4. Tuck in bottom of seat cover between seat backrest and metal bar (see NOTE 4)
5. With seat cushion in up position locate the straps (from step 3.) and secure to velcro tabs on seat cover (see NOTE 5)

- 6) Tuck in the 3 velcro straps through crevice and loop around the metal bar and secure (see NOTE 6)
- 7) Secure side velcro to the carpet side of seat backrest
- 8) Adjust all velcro for a uniform fit
- 9) Reinstall headrests (see NOTE 7)

NOTES:

<p>1) SELF-LOCKING SUPER-GRIP® BUCKLE:</p> 	<p>5)</p> 
<p>2) HEAD REST REMOVAL: A) - Insert paper clip into holes at base to release - Lift off OR B) - Push in side release buttons - Lift off (If unable to remove consult dealership)</p> 	<p>6)</p> <p>Diagram F</p> 
<p>3) Due to restricted space, a 4" x 30" piece of cardboard with 2 slits at one end will simplify the placing of the straps. If desired, the strip can be cut from the seat cover box.</p> 	<p>7) RE-INSTALLATION OF HEADRESTS A) Ensure pre-cut holes in seat cover align with holes in base. B) Replace headrests</p>
<p>4)</p> 	

WARNING: NEVER INSTALL SEAT COVERS ON SEATS WITH BUILT-IN AIRBAGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS WHICH COULD RESULT IN SERIOUS INJURY.



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438
 Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com