

If you have any comments or concerns,
please feel free to contact our
customer service department at:
Toll-free: 1-800-835-0438
OR
Email: info@gofia.com

**CUSTOM SEAT COVERS
BY**



**FEATURING
SUPER-GRIP® THE SLIP RESISTANT FASTENING SYSTEM**

**INSTALLATION INSTRUCTIONS
FOR
TR49-5, OE39-5, SL69-5, SP89-5**

Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit. The **Super Grip Buckles** are self-locking. For proper usage, see diagram.

INSTRUCTIONS:

A) BACKREST COVERS – “40” PORTIONS:

- | | |
|--------------------------------------|---|
| 1) Open zipper closure in seat cover | 4) Tuck flap through crevice and attach to velcro at back |
| 2) Install cover under seat belt | 5) Adjust velcro to equalize tension |
| 3) Close zipper (see note) | |

B) CUSHION COVER - “40” PORTIONS:

- | | |
|---|--|
| 1) Center cover on the seat | 3) Pass side straps around back of seat and buckle |
| 2) Pass the front strap under seat and buckle | 4) Adjust straps and buckles to equalize tension |

C) CUSHION COVER – “20” PORTION:

- | | |
|---|---|
| 1) Center cover on the seat | 4) Pass the side straps under back corners of center seat and secure to end buckles |
| 2) Tuck the back part of cushion cover through seat crevice | 5) Adjust straps and buckles to equalize tension |
| 3) Pass the front straps under the seat and secure to center buckle | |

D) BACKREST COVER – “20” PORTION:

- | | |
|---|---|
| 1) Open armrest / business console | 4) Snug cover at back of armrest so that the velcro attached to cover meets the metal hinge |
| 2) Center cover under armrest | 5) Secure the adhesive velcro to the hinge to align with velcro on cover |
| 3) Position adhesive backed velcro (supplied) to align with the velcro on cover | |

NOTES:

1) SELF-LOCKING SUPER-GRIP® BUCKLE:



3) SEATS WITH RELEASE LEVERS AND POWER CONTROLS:

- A) Locate levers or controls once seat cover is installed
- B) Slit hole(s) into the stretch fabric. **THE STRETCH FABRIC WILL NOT RUN**

2) ZIPPER:

- A) For ease in installation, the zipper is longer than the cover. Tuck excess zipper under cover.

WARNING: NEVER INSTALL SEAT COVERS ON SEATS WITH BUILT-IN AIRBAGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS WHICH COULD RESULT IN SERIOUS INJURY.

