

If you have any comments or concerns,
please feel free to contact our
customer service department at:
Toll-free: 1-800-835-0438
OR
Email: info@gofia.com

SEAT COVERS
BY

FEATURING

SUPER-GRIP®

THE SLIP RESISTANT FASTENING SYSTEM

INSTALLATION INSTRUCTIONS
FOR
TR42-19, Oe32-19, SP82-19

Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

INSTRUCTIONS:

A) BACKREST COVERS:


- 1) Remove center seat belt strap from the base (see note below)
- 2) Remove headrests (see note below)
- 3) Slip cover over backrest. Holding cushion up in ¾ position allows for better access
- 4) With cushion down, feed straps behind the seat
- 5) Smooth cover tightly from top to bottom
- 6) Locate straps and secure to buckles on seat cover
- 7) Tuck bottom of cover through crevice under backrest and tighten straps and buckles
- 8) Locate bottom right flap through crevice and hold at back of seat.
- 9) With other hand bring the side flap around and attach (see note below)
- 10) Repeat on other side
- 11) Adjust all straps, buckles and velcro to ensure a snug fit
- 12) Re-install headrests (see note below)

B) CUSHION COVERS:

- 1) Center cover on the seat. Cover has allowance for seat belt buckle
- 2) Tuck back flap through crevice
- 3) Lift seat and pass the front strap under seat and buckle
- 4) Pass side straps around the back and buckle
- 5) Adjust straps and buckles to equalize tension and ensure a snug fit
- 6) Replace center seat belt strap on base

NOTES:

1) SELF-LOCKING SUPER-GRIP® BUCKLE:




2) HEAD REST REMOVAL:

- A) - Insert paper clip into holes at base to release
- Lift off

OR


- B) - Push in side release buttons
- Lift off

(If unable to remove consult dealership)




2) REMOVAL OF CENTER SEAT BELT STRAP

- A) Insert paper clip into slot at base to release and lift



3) BOTTOM FLAP INSTALLATION



4) RE-INSTALLATION OF HEADRESTS

- A) Ensure pre-cut holes in seat cover align with holes in headrest base.
- B) Replace headrests

WARNING: NEVER INSTALL SEAT COVERS ON SEATS WITH BUILT-IN AIRBAGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS WHICH COULD RESULT IN SERIOUS INJURY.

Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com

2-5-09