

THANK YOU FOR SELECTING A HUSKY FLOOR LINER FROM Husky Liners, Inc

CARE AND USE INSTRUCTIONS

Your new liner is custom molded to fit your vehicle. Upon removal from the box your liner will not completely unroll and lay flat. This is normal and only temporary. Just place the liner on the floor or in the back of your vehicle with a weight in each corner (a book works well). After about 15 minutes, your liner will remain flat. In colder climates this “relaxing” may take longer; moving the liner inside will speed up the process.

Your liner is manufactured using an engineering resin that is lightweight and extremely tough and durable. The easiest way to clean your liner is with a damp cloth or sponge. If using a cleaner, 409® or Glass Plus® work well. Use of Armor All®, Son-of-a-Gun® or similar items is discouraged as these products make the liner slick.

CARGO LINER INSTALLATION INSTRUCTIONS FOR YOUR GRAND CARAVAN//TOWN & COUNTRY VAN WITH FOLD FLAT THIRD ROW SEAT

FRONT OF VEHICLE



NOTE: TO INSTALL YOUR HUSKY LINER CARGO LINER PART #4027, YOU MUST FIRST FOLD THE THIRD ROW STOW-N-GO SEATS OUT OF THEIR STORAGE WELL. ONCE THIS IS DONE SIMPLY PLACE YOUR CARGO LINER INTO THE WELL THE SEATS FOLDED OUT OF. YOU CAN STOW YOUR THIRD ROW SEATS BACK INTO THEIR STORAGE WELL WITH YOUR HUSKY LINER CARGO LINER INSTALLED.