



## Original Bar Grille

For proper installation and best possible fit, please read all instructions **BEFORE** you begin.  
For technical assistance or to obtain missing parts, please call Customer Relations at 1-800-328-5863.

### Important Safety Information




CAUTION  
PRECAUCIÓN  
ATTENTION

#### To avoid risk of personal injury or property damage:


- Wear safety glasses and gloves while installing billet inserts.
- Use caution when working with any power tools.
- Check clearance on vehicle.
- Make sure that the billet inserts are secured in place and clears all moving parts of the vehicle.
- Routinely check security of hardware.
- Do not use automatic “brush-style” car washes.

### Contents


Illustrations may vary upon application




2 - 1/4-20 x 3/4" (G51) Cap Screws



2 - 10/32 x 1" Button Head Socket Cap Screws



2 - 1/4 x 3/4" (W3) Washers



2 - 3/16 x 1/2" (W2) Washers




2 - 1/4-20 (N3) Nylon Lock Nuts



2 - 10/32 (N6) Kep Nuts




### Tools Required



Safety Glasses  
and Gloves



1/8" Hex Key



Ratchet with  
3/8 & 7/16" Sockets

### Shipping Note

Sometimes the billet products get bent in the shipping process. You may need to hand bend them to attain the desired shape.

# Installation Steps

Illustrations may vary upon application

Remove stock hardware and then remove the stock grille from the shell.

Place the billet grille into vehicle from the front (see diagram 1).

Secure the top tabs with the bolts provided. Some grille tabs may need to be mounted from the back of the core support or the front of the core support depending on the year of the vehicle.

Attach the bottom (see diagram 2) with screws provided and reinstall the grille shell back to the vehicle.

Diagram 1





Diagram 2



## Care and Cleaning

To keep your billet inserts looking their best, we recommend using only mild soap and water and a soft cotton cloth to wash and dry it. Use of rough cleaning agents or cloths may scratch or dull your billet inserts.

Should your billet inserts become scratched or dull, we recommend TRENZ® Metal Polish to bring back the mirror finish. There are three grades of TRENZ® Metal Polish (Coarse, Medium and Fine) that will help you keep your billet inserts looking brand new. Select the TRENZ® Metal Polishes best for your needs:

1. Course (Red) Polish – For severe scratches and pitted problems.
2. Medium (Green) Polish – For light scratches and dulling problems.
3. Fine (White) Polish – To bring back the mirror finish.

TRENZ® Metal Polish can be used on all metal products, including aluminum, stainless steel, brass and copper. If you have additional questions or concerns on the maintenance of your Lund® billet inserts, please call us at 800-328-5863. You may also use high quality commercially available polish recommended for aluminum accessories.

## Congratulations!

You have purchased one of many quality Lund® branded products offered by Lund International, Inc. We take the utmost pride in our products and want you to enjoy years of satisfaction from your investment. We have made every effort to ensure that your product is top quality in terms of fit, durability, finish and ease of installation.



Lund International, Lund Accessories Division  
775 Tipton Industrial Drive, Building 2, Suite F  
Lawrenceville, GA 30045

Phone 800-328-5863 • Fax 800-782-5448 • Visit us at [lundinternational.com](http://lundinternational.com)

© 2005 Lund International, Inc. All rights reserved.  
Lund® and the Lund® logo are trademarks of Lund International, Inc.

