Installation Instructions

Part Number 84127

Care and Cleaning

To keep your billet grille looking their best, we recommend using only mild soap and water and a soft cotton cloth to wash and dry it. Use of rough cleaning agents or cloths may scratch or dull your billet grille.

Should your billet grille become scratched or dull, we recommend TRENZ® Metal Polish to bring back the mirror finish. There are three grades of TRENZ® Metal Polish (Coarse, Medium and Fine) that will help you keep your billet grille looking brand new. Select the TRENZ® Metal Polishes best for your needs:

1. Course (Red) Polish – For severe scratches and pitted problems.

- 2. Medium (Green) Polish For light scratches and dulling problems.
- 3. Fine (White) Polish To bring back the mirror finish.

TRENZ® Metal Polish can be used on all metal products, including aluminum, stainless steel, brass and copper. If you have additional questions or concerns on the maintenance of your Lund® billet grille, please call us at 800-328-5863. You may also use high quality commercially available polish recommended for aluminum accessories.

Congratulations!


You have purchased one of many quality Lund® branded products offered by Lund International, Inc. We take the utmost pride in our products and want you to enjoy years of satisfaction from your investment. We have made every effort to ensure that your product is top quality in terms of fit, durability, finish and ease of installation.



Lund International, Lund Accessories Division 775 Tipton Industrial Drive, Building 2, Suite F Lawrenceville, GA 30045 Phone 800-328-5863 • Fax 800-782-5448 • Visit us at lundinternational.com

@ 2005 Lund International, Inc. All rights reserved. Lund $\ensuremath{\mathbb{R}}$ and the Lund $\ensuremath{\mathbb{O}}$ logo are trademarks of Lund International, Inc.






Sometimes the billet products get bent in the shipping process. You may need to hand bend them to attain the desired shape.


Installation Steps Illustrations may vary upon application

Remove the four (4) screws with a Phillips screwdriver and save them for reinstallation.

Behind the grille shell, there are two steel clips holding the bottom of the grille shell. Using a flat head screwdriver, pull upward on the bottom of the clip and pull the grille shell forward.



Clip the bottom of the grille shell back on the truck and secure the top of the grille using the four (4) screws that were removed in the first step. Make sure everything is secured and close the hood. Enjoy your award-winning grille that you have just installed!



4