XSVI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

X5VI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

X5VI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio. Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

X5VI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

XSVI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio. Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

XSVI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

XSVI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

X5VI-2103 INSTALLATION INSTRUCTIONS

In the GM vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-2103 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-2103. NOTE: The XSVI-2103 does not retain the factory warning chimes or the Drivers Information Center (D.I.C.) that is provided by the factory radio, Onstar, or the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-2103: Wiring up the XSVI-2103 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

I APPLICATIONS I

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07

(Except Classsic)

PONTIAC

G6 2005-07 Torrent 2006

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS I

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

2005-07 G6 2006 Torrent

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

G6 2005-07 Torrent 2006

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS I

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

2005-07 G6 Torrent 2006

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS I

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

2005-07 G6 2006 Torrent

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS

CHEVROLET

Cobalt 2005-06 Equinox 2005-06 Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

G6 2005-07 2006 Torrent

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS

CHEVROLET

Cobalt 2005-06 2005-06 Equinox Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

2005-07 G6 2006 Torrent

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS I

CHEVROLET

Cobalt 2005-06 2005-06 Equinox Malibu/Malibu Maxx 2004-07 (Except Classsic)

PONTIAC

2005-07 G6 2006 Torrent

REV. 05/29/07 INSTXSVI-2103 1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007