X5VI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520.

INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

factory amplifier if so equipped.

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com

1-800-221-0932 www.metraonline.com Metra Electronics Corporation © Copyright 2007

X5VI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

X5VI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com Metra electronics corporation © copyright 2007

X5VI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com Metra Electronics Corporation © Copyright 2007

XSVI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

<u>X5VI-5520</u> INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

XSVI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

X5VI-5520 INSTALLATION INSTRUCTIONS

In the Ford and Lincoln vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-5520 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-5520. NOTE: The XSVI-5520 does not retain use of the factory amplifier if so equipped. INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off. Wiring the XSVI-5520: Wiring up the XSVI-5520 is like wiring up any other wire harness that would attach to the aftermarket radios harness. The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)
REV. 11/06/07 INSTXSVI-5520

1-800-221-0932 www.metraonline.com METRA ELECTRONICS CORPORATION © COPYRIGHT 2007

APPLICATIONS

FORD Edge Escape Expedition	2007 2008 2007
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006
MAZDA Tribute MERCURY Mariner	2008

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS I

FORD Edge Escape Expedition	2007 2008 2007	
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006	
MAZDA Tribute MERCURY Mariner	2008	

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

FORD Edge Escape Expedition	2007 2008 2007
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006
MAZDA Tribute MERCURY	2008
Mariner	2008

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS I

FORD Edge Escape Expedition	2007 2008 2007
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006
MAZDA Tribute	2008
MERCURY Mariner	2008

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

FORD Edge Escape Expedition	2007 2008 2007
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006
MAZDA Tribute	2008
MERCURY Mariner	2008

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS I

FORD		
Edge	2007	
Escape	2008	
Expedition	2007	
LINCOLN		
MKX	2007	
MKZ	2007	
Navigator	2007	
Zephyr	2006	
MAZDA		
Tribute	2008	
MERCURY		
Mariner	2008	

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

2007 2008 2007
2007 2007 2007 2006
2008
2008

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

FORD Edge Escape Expedition	2007 2008 2007	
LINCOLN MKX MKZ Navigator Zephyr	2007 2007 2007 2006	
MAZDA Tribute	2008	
MERCURY Mariner	2008	

REV. 11/06/07 INSTXSVI-5520
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007