



P/N 11503.21 (Black)

Rock Crawler Classic Rear Bumper (With Tire Carrier)
For 87-06 Jeep® YJ & TJ Wrangler

Important notice:

Carefully read instructions before attempting to install this product. Rugged Ridge is in no way responsible for any damage to the vehicle or personal injury that may occur during the installation or use of this product.



NO DRILLING REQUIRED.

Supplied components (Box 1) Bumper:

Rear bumper p/n: 11503.20	(1)	3/8" x 1 1/4" Hex head bolts	(8)
Backing plates	(4)	3/8" Flat Washers	(8)
3/8" Locking Washer	(8)	7/16" x 1 1/4" Hex head bolt	(2)
7/16" Flat Washer	(2)	7/16" Lock Washer	(2)

Supplied components (Box 2) Tire Carrier:

Tire Carrier	(1)	Post Bar	(1)
Tire Mount Bracket	(1)	Circle Clip	(1)
3/8"-24x1" Hex Head Bolt	(3)	3/8"-24x1 1/4" Hex Head Bolt	(2)
3/8" Flat Washer	(10)	3/8" Nylock Nuts	(5)
3/4"x3" Hex Head Bolt	(1)	3/4" Flat Washer	(2)
3/4" Nylock Nut	(1)	1/4"-20 Lug Nuts	(3)

Installation Instructions:

(Step 1): Remove factory rear bumper if equipped. For some TJ applications the rear body mount bolt and bushing may be removed to ease installation. (Fig.1 and Fig.2)

Fig. 1



Fig.2






(Step 2): Locate (2) backing plates, (4) 3/8" Hex head bolts, (4) 3/8" Flat washers, and (4) 3/8" Lock washers. With the help of another person attach backing plates to the rear vehicle frame. Align holes in the rear plate on the Classic Rock Crawler bumper to those existing in the frame. Loosely attach to one side of vehicle with hardware listed in this step. (See Fig.3)

(Step 3): Repeat step two for opposite side, loosely attach bolts but do not tighten at this time.
NOTE: Lower mounting brackets (one per side) should align with existing lower Cross member holes.

(Step 4): Locate (1) 7/16" Hex head bolt, (1) 7/16" Flat washer, and (1) Lock washer. Attach and Secure bottom bracket to cross member with hardware listed in this step.

(Step 5): Repeat step 4 for opposite side. At this time align bumper correctly and tighten all mounting hardware. **NOTE: It is important to periodically check all bolts for tightness.**

ON SOME TJ MODELS DROPPING OF THE FUEL TANK – GUARD/ SKIDPLATE WILL EASE INSTALLATION OF BRACKETS. BE SURE TO FOLLOW FACTORY DIRECTIONS FOR DROPPING THE FUEL TANK.



Note: Please take care when assembling and installing this product to protect the finish and your investment. To protect the bumpers finish wax after installation. Regular waxing is recommended. DO NOT use any type of cleaner or wax that contains abrasives that could damage the finish






Tire Carrier installation Instructions:

(Step 6): With the assistance of another person, secure the tire carrier to the bumper pivot spindle. Work tire carrier all the way down onto the spindle (circle clip groove should be visible) and close. Install (2) 3/8" - 24 x 1 1/4" Hex Head Bolts, (4) 3/8" Flat Washers, and (2) 3/8" Nylock Nuts to the tire carrier arm clamp. (Fig.5 & 6)

Fig.5



Fig.6



(Step 7): Install the circle clip onto the top of spindle and seat into groove (Fig.6). Install grease nipple. Add grease using grease gun to lubricate the spindle and pivot clamp before use.

NOTE: Spindle and pivot clamp should be greased as part of your regular vehicle maintenance.

(step 8): Install post bar at this time to the top of the tire carrier. Use (1) 3/4" x 3" Hex Head Bolt, (2) 3/4" Flat Washers, and (1) 3/4" Nylock Nut.

(Step 9): Locate tire mount bracket and install using (3) 3/8"-24 x 1" Hex Head Bolts, (6) 3/8" Flat Washers, and (3) 3/8" Nylock Nuts. Slide mount onto tire carrier and hand tighten. There are two sets of mounting slots on the tire carrier. With the post bar installed test fit the spare tire and determine what is the best mounting point for your tire size and vehicle. Tighten all bolts.

NOTE: When the spare tire is installed it should be set snugly against the post bar. For most over sized tires the outer mounting holes will be used. TIRE CARRIER can be used with tires up to 35" in diameter.

Note: Please take care when assembling and installing this product to protect the finish and your investment. To protect the bumpers finish wax after installation. Regular waxing is recommended. DO NOT use any type of cleaner or wax that contains abrasives that could damage the finish

Fig. 3



LIMITED 90 DAY WARRANTY
Applies to Rugged Ridge by Omix-ada Inc. Products

Rugged Ridge Off Road (the Company) warrants to the original purchaser of this product that should the product or any part thereof, under normal use and conditions, be proven defective in material or workmanship within 90 DAYS from the date of original purchase, such defect(s) will be repaired or replaced or credited at the Company's sole option.

To obtain repair or replacement within the terms of this Warranty, the product is to be delivered with proof of warranty coverage (e.g. Dated bill of sale), specification of defect(s) to the place of purchase or, with prior approval from the Company (Return Authorization Number is required), freight pre-paid to the Company address listed below.

This warranty does not apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through alteration, improper installation, mishandling, misuse, neglect, accident or by acts of nature. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY PURCHASER FOR THE PRODUCT.

This Warranty is in lieu of all express warranties or liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHT WITHIN THE PERIOD OF 90 DAYS FROM DATE OF ORIGINAL PURCHASE.

IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WHATSOEVER. No person or representative is authorized to assume for the Company any liability other than expressed herein in connection with the sale of this product.

Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Omix-ada Inc.
460 Horizon Dr. Suite 400
Suwanee, Georgia 30024

