

**Rugged
Ridge**

**OUTLAND
AUTOMOTIVE**

P/N: 13265.01

Installation instructions

2007-08 Jeep® Wrangler JK - Neoprene Rear Seat Covers
2-Door Rear Seats

13265.04

13265.09

13265.53

Parts included: (1) Rear top cover
(1) Rear bottom cover
(2) Head Rest Covers

NOTE: Please read instructions before installing

Instructions:

Step (1) Remove rear headrest from seat. The headrest can be removed by pressing the two buttons located on the top of the seat.

Step (2) Slip upper seat cover over rear seat. Note location of headrest mounting holes. Slip lower Velcro strip between the upper and lower portions of the seat and secure. Connect zipper and close.

Step (3) Push seat cover over headrest mounting plates. Secure under plastic caps as shown.

Step (4) Adjust upper seat cover as needed for proper fitment.

Step (5) Slip lower cover over seat bottom and slide back clips and straps through the gap between the top section and the lower seat section. Fold and touble the seat so that front to rear straps can be secured.

Step (6) With seat folded forward loosen steps and attach front strap to back clip. Repeat for all three locations.


Step(1)



Step (2)



Step (3)





Step (6)

Step (7) With straps attached carefully pull straps to tighten.

NOTE: DO NOT OVER TIGHTEN
Damage to seat cover may result.



Step (8) Slide side clips between the seat and the fenderwell and secure. Fold seat back down and check fitment of cover noting carseat attachment slots.
Adjust as needed.

Step (9)

Step (10)

Step (9) Slide supplied headrest covers over headrest and secure velcro.
Adjust fitment as needed.



Step (10) Insert headrest back onto rear seat.

Step (11) Inspect seat cover and adjust as needed. You may need to fold and tumble the seat several times and adjust to get the final fitment.

Step (11)





LIMITED 90 DAY WARRANTY

that should the product or any part thereof, under normal use and conditions, be proven defective in material or workmanship within 90 DAYS from the date of original purchase, such such defects will be repaired or replaced or credited at the Company's sole option.

To obtain repair or replacement within the terms of this Warranty, the product is to be delivered with proof of warranty coverage (e.g. Dated bill of sale), specification of defects) to the place of purchase or, with prior approval from the Company (RGA Number is required), freight pre-paid to the Company address listed below.

This warranty does not apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through alteration, improper installation, mishandling, misuse, neglect, accident or by acts of nature. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY PURCHASER FOR THE PRODUCT.

This Warranty is in lieu of all express warranties or liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHT WITHIN THE PERIOD OF 90 DAYS FROM DATE OF ORIGINAL PURCHASE.

IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WHATSOEVER. No person or representative is authorized to assume for the Company any liability other than expressed herein in connection with the sale of this product.

Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Omix-ada Inc.
460 Horizon Dr. Suite 400
Suwanee, Georgia 30024