

Installation Instructions

Sure Steps (Part # CN012-S4) 1992-1999 Suburban 4 Door

QTY	PART #	DESCRIPTION
1	CN012-S4L	Sure-Step, left side
1	CN012-S4R	Sure-Step, right side
1	603722	hardware kit
1	720009	warranty statement

NOTE: Please read this information before installing. Check components received with components listed above. **NO DRILLING REQUIRED** for installation of these Sure-Step side bars. To obtain correct installation, we recommend you to follow these step by step installation instructions carefully. Please take care when installing this product to protect the finish and your investment. For Technical Support please call (951) 736 8686.

Step One: Locate hardware marked 603722. Check contents of 603722 with the hardware listed below.

2 901119 12mm x 1.75mm x 120mm hex bolts 6 901011 1/2 flat washers 6 901012 1/2 split lock washers 4 000000 1/2-13 x 2" hex bolts, GR.5 2 901132 2 1/2 od. spacers, zinc plated 4 #30 3" plastic rings 1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side 1 801357R rear support bracket, right side	QTY	PART#	DESCRIPTION
6 901012 1/2 split lock washers 4 000000 1/2-13 x 2" hex bolts, GR.5 2 901132 2 1/2 od. spacers, zinc plated 4 #30 3" plastic rings 1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side	2	901119	12mm x 1.75mm x 120mm hex bolts
4 000000 1/2-13 x 2" hex bolts, GR.5 2 901132 2 1/2 od. spacers, zinc plated 4 #30 3" plastic rings 1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side	6	901011	1/2 flat washers
2 901132 2 1/2 od. spacers, zinc plated 4 #30 3" plastic rings 1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side	6	901012	1/2 split lock washers
4 #30 3" plastic rings 1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side	4	000000	1/2-13 x 2" hex bolts, GR.5
1 801086L front support bracket, left side 1 801086R front support bracket, right side 1 801357L rear support bracket, left side	2	901132	2 1/2 od. spacers, zinc plated
1 801086R front support bracket, right side 1 801357L rear support bracket, left side	4	#30	3" plastic rings
1 801357L rear support bracket, left side	1	801086L	front support bracket, left side
	1	801086R	front support bracket, right side
1 801357R rear support bracket, right side	1	801357L	rear support bracket, left side
	1	801357R	rear support bracket, right side

Step Two: Locate the CN012-S4L side bar, one 801086L support bracket, one #30 plastic ring, two ½ x 2" hex bolts, two ½" flat washers and two ½" split lock washers. Secure the bracket and ring to the side bar using the hardware listed in this step. (Fig #1) Do not fully tighten hardware at his time. Repeat this procedure on the other end of the side bar using the 801357L support bracket.

Step Three: Locate one 901132 spacer, one 12mm hex bolt, two ½" flat washers and one ½" split lock washer. Remove the front cab mount bolt located under the cab. Remove the rear spring hanger nut. "CAUTION" do not remove the rear spring hanger bolt, doing so could result in injury or damage to the vehicle. Place the spacer over the spring hanger bolt and position the rear support bracket over the rear spring hanger bolt. Secure the support bracket and spacer to the spring hanger with the factory nut as shown in fig #2. Do not fully tighten the nut at this time. Position the front support bracket under the front cab mount. Secure the support bracket to the bottom of the cab mount as shown in fig #3 using the remaining hardware listed in this step. Fully tighten all hardware at this time. Torque part 901119 to 50 ft. lbs., 901030 to 30 ft. lbs. and the rear spring hanger nut to 80 ft. lbs.

For Technical Support/Warranty Information please call 310-762-9944



Installation Instructions

Sure Steps (Part # CN012-S4) 1992-1999 Suburban 4 Door








Fig #1 Fig #2 Fig #3

(Photos are for reference only, actual brackets may be different)

Step Four: Repeat steps two and three on opposite side of vehicle.

Be sure to use all hardware supplied and tighten all bolts.

IMPORTANT: Sure-Step side bars have a 300 lb. weight capacity. To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish.

Product cleaning and maintenance instructions

Stainless Steel Finish – Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean the finish. Dual state powder coat finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you may wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish. Textured coated finishes should be cleaned with a mild soap on a damp sponge. Do not apply polish or was that requires to be removed by means of buffing. This type of wax is commonly used at car wash facilities. Chrome Finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish you should wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish.

Smittybilt's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, Smittybilt warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on-road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. Smittybilt is not responsible for items damaged during

For Technical Support/Warranty Information please call 310-762-9944



Installation Instructions

Sure Steps (Part # CN012-S4) 1992-1999 Suburban 4 Door

shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. Smittybilt strongly recommends returning the warranty registration card.

Customer's remedy hereunder shall be limited only to repair or replacement (at Smittybilt's option) of any defective part(s) returned to Smittybilt at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at Smittybilt's sole discretion.

Duration of Limited Warranty

1. Limited Lifetime Warranty on Stainless Steel Products -

Smittybilt stainless steel products carry the foregoing limited repair or replacement warranty against workmanship and defects in the material so long as the original purchaser retains the original stainless steel parts.

2. Limited Five (5) Year / 50,000 Mile Pro-Rata Warranty (whichever occurs first) on Dual-Stage Powder Coating Products -

Smittybilt dual-stage powder coated products carry the foregoing limited repair or replacement warranty for a period of (5) years or 50,000 miles (whichever occurs first) from date of purchase against workmanship and defects in the material, provided that any claim submitted after (2.5) years from date of purchase shall, if accepted, be satisfied by Smittybilt offering customer a credit on the purchase of a replacement product equal to fifty percent (50%) of customer's initial purchase price.

3. Limited Three (3) Year / 36,000 Mile Pro-Rata Warranty (whichever occurs first) on Chrome Products -

Smittybilt chrome products finished carry the foregoing limited repair or replacement warranty for a period of three (3) years or 36,000 miles against workmanship and defects in the material (whichever occurs first) from the date of purchase.

Requesting Warranty Coverage

To make a claim under this limited warranty, customer must:

(1) Call Smittybilt, at (888) 717-5797 for a return authorization code (RAC) and/or Smittybilt may require photographic proof of defect before issuing an (RAC); (2) return the defective part, properly packaged to prevent further damage to the product, postage prepaid, together with dated proof of purchase receipt and identifying return authorization code (RAC) on the outside of the packaging to Smittybilt at 1600 Walnut Parkway, Compton, CA 90220. Warranty claims can not be determined until the returned merchandise is inspected. A minimum charge of fifteen percent (15%) may be added for all products which are determined to be returned for reasons other than warranty. Additional charges may be applied if merchandise is damaged or unsellable upon receipt.

For Technical Support/Warranty Information please call 310-762-9944