

Installation Instructions

Sure-Step (Part # CN180-S4) 88-98 C/K Pickup Extended Cab

| QTY | DESCRIPTION |
|-----|----------------------|
| 1 | Side Bar, left side |
| 1 | Side Bar, right side |
| 1 | Hardware Kit |

NOTE: Please read this information before installing. Check components received with components listed above.

SOME DRILLING REQUIRED for installation of these Side Bars. To obtain correct installation, we recommend you to follow these step by step installation instructions carefully. Please take care when installing this product to protect the finish and your investment. For Technical Support call (951) 736-8686

Step One: Locate hardware kit. Check contents with the hardware listed below.

| QTY | DESCRIPTION |
|-----|------------------------------------|
| 2 | Front Mounting Bracket-small |
| 2 | Rear Mounting Bracket-large |
| 2 | Support Bracket |
| 4 | 12mm x 50mm Hex Bolt-zinc plated |
| 8 | 12mm Lockwasher-zinc plated |
| 8 | 12mm Flatwasher-zinc plated |
| 2 | 10mm Hex Nut-zinc plated |
| 4 | 10mm Flatwasher-zinc plated |
| 2 | 10mm Lockwasher-zinc plated |
| 2 | 10mm x 32mm Hex Bolt-zinc plated |
| 4 | 12mm x 110mm Hex Bolts-zinc plated |
| 4 | 3" Plastic Rings |
| | |

Step Two: Remove the four body mount bolts.

Step Three: Attach the front and rear mounting brackets to the body mounts with the 12mm bolts, 12mm flatwashers, and 12mm lockwashers as shown in the drawing and hand tighten.

<u>Step Four</u>: Place the side bars into position. (NOTE: To determine which side bar is the left or right, check the number on the welded insert at the end of the tube.)

Step Five: Attach the side bars to the mounting brackets with the 12mm hardware and 3" plastic rings provided.

Step Six: Remove the 12mm x 50mm bolts holding the end of the side bar to the rear mounting bracket. Put the short end of the support bracket up to the backside of the rear mounting bracket and attach it with the 12mm hardware previously removed.. Orient the bracket so that the long end touches the bottom of the frame. Using the hole in the long end of the bracket as a guide, drill a 7/16" hole in the bottom of the frame and attach it with the 10mm hardware provided.

<u>Step Seven</u>: After checking to make sure the side bars are level and square with the side of the vehicle completely tighten all hardware.

Step Eight: Periodically check and retighten the hardware as necessary.

For Technical Support/Warranty Information please call 310-762-9944



Installation Instructions

Sure-Step (Part # CN180-S4) 88-98 C/K Pickup Extended Cab

Cleaning and Maintenance

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used also.

For gloss black finishes: Mild soap, window and glass cleaner may be used.

LIMITED WARRANTY

Smittybilt (The Company) warrants to the original purchaser of this product that should the product or any part thereof, under normal use and conditions, be proven defective in material or workmanship within the warranty period of 5 years from the date of purchase, such defect(s) will be repaired or replaced (At the Company's option) without charge for parts or labor. To obtain repair or replacement within the terms of the warranty, the product is to be delivered with proof of warranty coverage (e.g. dated bill of sale, receipt), specification of defect, freight pre-paid with Returns Good Authorization Number from Smittybilt to place of purchase. Items returned to Smittybilt without a Returns Authorization Number will be refused and returned to sender at the senders' expense.

This warranty does not apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through altercation, improper installation, mishandling, misuse, neglect accident or acts of nature. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY THE PURCHASER FOR THIS PRODUCT.

This warranty is in lieu of all expressed warranties and liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHTH WITHIN A PERIOD OF 90 DAYS FROM DATE OF ORIGINAL PURCHASE.IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, WHATSOEVER. No person or representative is authorized to assume for the company any liability other than expressed herein in connection with the sale of this product. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, therefore above limitations may not apply to you. This warranty gives the purchaser specific legal rights. The purchaser may have additional rights, which vary from state to state.

Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, therefore above limitations may not apply to you. This warranty gives the purchaser specific legal rights. The purchaser may have additional rights, which vary from state to state.

For Technical Support/Warranty Information please call 310-762-9944