



Installation Instructions

Nerf Step (Part# D0989CC)
09-10 Dodge Crew Cab
Nerf-Step (Part# D0989QC)
09-10 Dodge Quad Cab



Hardware Kit Contains:

- 12) 3/8" x 1" hex bolts
- 12) 3/8" Flat Washers
- 12) 3/8" Threaded Clips

Recommended Tools:

- 9/16" Socket Wrench
- Drill- 1" hole saw

Step 1: Locate the driver side nerf-step by matching the shorter tail bend to the front of the vehicle. **NOTE:** Some models have a straight cut end with a cap, that end will face the rear tire.

Step 2: Starting with the driver's side, locate the six factory mounting hex holes (which are positioned on the vertical side of the floor pan below the doors) with two in the front, two in the middle, and two towards the rear of the body.

Step 3: Mark and drill a pilot hole in the center between each factory hex head hole. Next, in each pilot hole, drill a 1" hole using a 1" hole saw. Using the 3/8" threaded clips, slide two clips in each 1" hole outward, so the threaded part is visible through the hex holes. **SEE FIGURE 1.**




Fig. 1

Step 4: Align the nerf-step up to the body where the three brackets on the nerf-step match up to the six threaded locations. Next, start all six 3/8" x 1" hex bolts, flat washers and finger tighten.

Step 5: Starting with the front, push the nerf-step up and torque the front bolt to 15-20 ft/lbs, level the rear tail section and then torque the very rear bolt. Finally, tighten all remaining bolts in between. Repeat on passenger side. This concludes the installation. Questions? Call 281-880-6322

For Technical Support/Warranty Information please call 310-762-9944



Installation Instructions

Nerf Step (Part# D0989CC)

09-10 Dodge Crew Cab

Nerf-Step (Part# D0989QC)

09-10 Dodge Quad Cab

Products licensed to N-fab Inc. by Fichter Designs are protected by US patent law and International Copy Right law. US Patent law and International Copy Right law. US Patent # 6588783, # 6874801, # 7416202. Other patents and continuances pending. N-fab products configuration also protected by International Trade Dress Law. All Design and Patent infringements will be prosecuted to the full extent of the law.

Product cleaning and maintenance instructions

Stainless Steel Finish – Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean the finish. **Dual state powder coat finish** – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you may wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish

WARRANTY

Smittybilt's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, Smittybilt warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on-road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. Smittybilt is not responsible for items damaged during shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. Smittybilt strongly recommends returning the warranty registration card.

Customer's remedy hereunder shall be limited only to repair or replacement (at Smittybilt's option) of any defective part(s) returned to Smittybilt at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at Smittybilt's sole discretion.

1. Limited Lifetime Warranty on Stainless Steel Products -

Smittybilt stainless steel products carry the foregoing limited repair or replacement warranty **against workmanship and defects in the material** so long as the original purchaser retains the original stainless steel parts.

2. Limited Five (5) Year / 50,000 Mile Pro-Rata Warranty (whichever occurs first) on Dual-Stage Powder Coating Products -

Smittybilt dual-stage powder coated products carry the foregoing limited repair or replacement warranty for a period of (5) years or 50,000 miles (whichever occurs first) from date of purchase **against workmanship and defects in the material**, provided that any claim submitted after (2.5) years from date of purchase shall, if accepted, be satisfied by Smittybilt offering customer a credit on the purchase of a replacement product equal to fifty percent (50%) of customer's initial purchase price.

For Technical Support/Warranty Information please call 310-762-9944

Smittybilt, 400 West Artesia Blvd, Compton, CA 90220



Installation Instructions

Nerf Step (Part# D0989CC)

09-10 Dodge Crew Cab

Nerf-Step (Part# D0989QC)

09-10 Dodge Quad Cab

For Technical Support/Warranty Information please call 310-762-9944

Smittybilt, 400 West Artesia Blvd, Compton, CA 90220