

T-MAX[®]

MAXIMUM OFF-ROAD RECOVERY.™

T-MAX Synthetic Rope



M0803SR



FEATURES

- ✓ Made with Dyneema SK-75 fiber.
- ✓ 1/7th the weight of a steel wire rope of the same diameter.
- ✓ Floats, minimal weight-torque free.
- ✓ No kinks, curls or wire splinters.
- ✓ Minimal stretch, non-rotational.
- ✓ little lash-back occurs.
- ✓ UV Resistance.
- ✓ Abrasion resistance.
- ✓ Specially coated prevent from slipping off the winch drum.
- ✓ With sleeve prevents from heating.
- ✓ Specially costed for added heat resistance.



ITEMS&SPECIFICATIONS

	Specification (Dia×L)	Applicable Winch Capacity
<input type="checkbox"/>	7/16"×100'(11mm×30m)	
<input type="checkbox"/>	7/16"×50'(11mm×15m)	12000lbs
<input type="checkbox"/>	25/64"×94'(10mm×28m)	
<input type="checkbox"/>	25/64"×80'(10mm×24m)	10000lbs
<input type="checkbox"/>	25/64"×50'(10mm×15m)	
<input type="checkbox"/>	3/8"×94'(9.4mm×28m)	
<input type="checkbox"/>	3/8"×50'(9.4mm×15m)	9500lbs
<input type="checkbox"/>	23/64"×100'(9.1mm×30m)	
<input type="checkbox"/>	23/64"×50'(9.1mm×15m)	9000lbs
<input type="checkbox"/>	11/32"×100'(8.6mm×30m)	
<input type="checkbox"/>	11/32"×50'(8.6mm×15m)	8000lbs
<input type="checkbox"/>	5/16"×50'(8.1mm×15m)	6500lbs
<input type="checkbox"/>	1/4"×50'(6.3mm×15m)	4500lbs
<input type="checkbox"/>	19/64"×100'(7.5mm×30m)	
<input type="checkbox"/>	19/64"×50'(7.5mm×15m)	
<input type="checkbox"/>	1/4"×20'(6.3mm×6m)	

WARNINGS



Fiber rope will fail in case of worn, damaged, overloaded, or not properly maintained; The user is responsible to determine the suitability of a rope for specific applications; Use only rope in good condition, without cuts or pulled strands; Bear in mind the working load limitation of your rope; Do not exceed the working load limitation or shock load of your rope; Do not stand within the lash-back area; Do not use over rough surfaces without chafe protection; Do not bend around unprotected, sharp corners.