



Installation Instructions

Tail Light Guard P/N#39-3300/39-3305
04-07 Ford F-150 (Excl. Heritage Edition)

Part List:

Item number	Description	Quantity
1	Light Guard	2
2	ST6.3*30 Phillips Sheet Metal Screws	4
3	M6 Flat Washers	4

Note: Please protect the product from being scratched during the installation process.

Step One: Locate hardware and check contents with hardware listed above. Read instructions completely before beginning.

Step Two: Open the rear Tail Gate and remove the two screws securing the Taillight to the body. Save the factory screws to be reinstalled later.

Step Three: Carefully unsnap the Taillight and remove it from the body. While holding the Taillight housing position the Taillight Guard over the Taillight and hook the support tab to the edge of the lens.

Step Four: Align the mounting tabs with the holes in the Taillight and snap the assembly back into the body.

Step Five: Attach the assembly to the body using the existing factory screws. Carefully close the Tailgate and check for clearance. Tighten all fasteners at this time.

Step Six: Repeat Steps 1-5 on opposite side.

Westin Automotive Products, Inc.
5200N. Irwindale Ave. Suite 220
Irwindale, Ca. 91706

Thank You for choosing Westin products
For additional installation assistance please
call

Customer service (800) 345-8476 or (626) 960-6762