



Installation Instructions
Tail Light Guard P/N#39-3410/39-3415
02-06 Jeep Liberty

Part List:

Item number	Description	Quantity
1	Light Guard	2
2	M4*12 Phillips Screws	2
3	Support Brackets	2
4	M4 Flat Washers	2

Note: Please protect the product from being scratched during the installation process.

Step One: Locate hardware and check contents with hardware listed above. Read Instructions completely before beginning.

Step Two: Open the rear Lift Gate and remove the two Torx Head Screws securing the Taillight to the body.

Step Three: Carefully unsnap the Taillight and remove it from the body. Disconnect the wiring and place the Taillight on a protective surface.

Step Four: Remove the top attachment pin from the Taillight, position the Taillight Guard over the Taillight and hook the Support Bracket on the top edge.

Step Five: Align the Mounting Tabs with the holes in the Tail light and attach the Taillight Guard to the Taillight using the Attachment Pin and the #6 X 1/2" Screw.

Step Six: Reconnect the wiring and snap the assembly back into body.

Step Seven: Attach the assembly to the body using the Factory Torx Screws. Carefully close the Lift Gate and check for Clearance. Tighten all fasteners at this time.

Step Eight: Repeat Steps 1-7 on opposite side.



Thank You for choosing Westin products
For additional installation assistance please call
Customer service (800) 793-7846 or (507) 375-3559