

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**

## **5/16" Pressure Plate Bolts**

A small amount of threadlocking compound is recommended on all clutch fasteners.

DO NOT use a washer with this pressure plate bolt.

Tighten all bolts evenly, ¼ turn at a time in a crisscross pattern until pressure plate is completely drawn-up to the flywheel.

**Final torque to: 25 - 28 ft/lbs.**

**Note:** These specifications apply only to the fasteners supplied by Centerforce.

I01MI008 **CENTERFORCE TECH. LINE (928) 771-8422**