



INSTALLATION INSTRUCTIONS

MAKE: Dodge

MODEL: 1500

YEAR: 2009 - 2018

ENGINE: V8-5.7L HEMI

WHEELBASE: 140"

MAKE: RAM

MODEL: 1500

YEAR: 2011 - 2018

ENGINE: V8-5.7L HEMI

WHEELBASE: 140"

MAKE: Dodge / RAM

MODEL: 1500 Classic

YEAR: 2019

ENGINE: V8-5.7L HEMI

WHEELBASE: 140"

Y-Pipe

48-42003 (w/ Cats)

48-42004 (w/o Cats)

48-02003 (ALZ w/ Cats)

48-02004 (ALZ w/o Cats)

Left Y-Pipe Assembly

05-42907 (AL, w/Cat)

05-42909 (AL, w/out Cat)

05-44907 (SS, w/Cat)

05-44910 (SS, w/out Cat)

3" Band Clamp

05-41055

Mid-Pipe Assembly

05-42909 (AL)

05-44909 (SS)

3-1/2" Band Clamp

05-41171


Right Y-Pipe Assembly

05-42908 (AL, w/Cat)

05-42911 (AL, w/out Cat)

05-44908 (SS, w/Cat)

05-44911 (SS, w/out Cat)



RACE ONLY DISCLAIMER



This is a Race Only product that is to be used solely for competition, it cannot be used on vehicles that are operated on public streets, roads or highways. Its use is limited to closed-course and open-course racing that is formally sanctioned by a recognized racing organization. Any other use, including recreational off-road use, could be in violation of local, state and federal laws. A competition acknowledgement / liability release form must be filled out and submitted.

Caution: aFe recommends professional installation on our products. Allow time for your vehicle to cool down prior to installation. When working on or under your vehicle proceed with caution. Exhaust systems reach high temperatures and may cause serious burns. Wear protective safety equipment; eye goggles and gloves to ensure a safe installation.

- Step 1:** **(Read instructions prior to installation.)** For faster removal and installation of exhaust a trained professional is recommended for this procedure. Secure stock exhaust with jack/stands before removing. Please allow exhaust to cool down! This will prevent any burn injuries.
- Step 2:** Secure vehicle on jack stands (refer to your manual for specified jack stand positions).
- Step 3:** Disconnect the battery before starting work on the exhaust system.
- Step 4:** Loosen the muffler clamp on the exhaust system to muffler extension pipe.
- Step 5:** Remove exhaust from all hangers and remove from truck.
- Step 6:** Loosen the muffler clamp on the exhaust extension pipe to the Y-pipe.
- Step 7:** Remove the rubber hangers from the exhaust extension pipe remove the extension pipe.
- Step 8:** Un-plug O2 sensors on Y-pipe.
- Step 9:** Remove the (4) 10mm nuts on the Y-pipe to OE exhaust manifolds and remove OE Y-pipe.
- Step 10:** Install left aFe power, converter pipe and clamp on aFe power Right/Y-pipe merge.
- Step 11:** Remove O2 sensors from OE Y-pipe
(MARK O2's SO THEY GO BACK IN SAME CORRECT LOCATION).
- Step 12:** Install O2's sensors on afe power Y-pipe in the same location as the OE Y-pipe.
- Step 13:** Install aFe power Y-pipe to OE manifolds using the original (4) 10mm nuts make finger tight only at this time.
- Step 14:** Install the 3 1/2" band clamp on aFe power exhaust Extension pipe and install on aFe power Y-pipe on vehicle using the stock rubber isolation mounts.
- Step 15:** Tighten (4) 10mm nuts on aFe Y-pipe to OE exhaust manifolds.
- Step 16:** Tighten 3" band clamp on aFe power Y-pipe.
- Step 17:** Plug in O2 sensor connectors and make sure O2 sensors and wires are clear of heat shields.
- Step 18:** Re-install exhaust system and fasten to aFe power Y-pipe extension tube using the original muffler clamp and tighten.
- Step 19:** Tighten the 3-1/2" band clamp on aFe power Y-pipe extension tube.
- Step 20:** Re-connect battery.