

FUNCTION AND STYLE FOR TODAY'S TRUCKS

INSTALLATION INSTRUCTIONS #INST008:

BACKRACK KIT #30108, 30108TB, 30108TB31 1995-2007 Toyota Tundra

READ THIS NOW!

Your truck should look like the one shown. If you think you are missing any parts, think that this part number is not for your truck or have any installation question, call our customer service department at toll free:

800-265-8137 or locally 905 849-3633.

Other ways to reach BACKRACK:

Fax **905-849-4116**

email: techsupport@backrack.ca



The BACKRACK is secured to your truck with a pair of "Stake Pocket Bolts" specifically designed for your make and model of truck. These bolts mount into each of the two front stake pockets. The BACKRACK assembly sits on the bed rails of your truck and is secured to these Stake Pocket Bolts. If your truck has a BEDLINER we suggest you remove it to install the Stake Pocket Bolts

PARTS LIST FOR KIT #30108

PART	DESCRIPTION	QTY	
RMB503P	Rail Mount Bracket Passenger	1	
RMB503D	Rail Mount Bracket Driver	1	
RP503S	Rail Plate Symetrical	2	
HARDWARE BAG508			
INST008	Installation Instruction	1	
FYZ008	1/2"-20 Nylon Hex Lock Nut	2	
FYZ009	1/2"-13 Hex Nut	2	
FYZ010	1/2" Lock Waser	2	
FYZ011	1/2" Flat Washer	2	
FYZ012	1/2" Flat Washer Large	2	
FYZ014	1/2"-20 x 3.25" Carrige Bolt Grade 8	2	
FYZ016	5/8"-11 Hex Nut	2	
FYZ017	5/8" Lock Washer	2	
FYZ018	5/8" Flat Washer	2	
SBY508S	Stake Pocket Bolt	2	
SF002	2" x 6" Foam Pad	2	

PARTS LIST FOR KIT #30108TB, 30108TB31

PART	DESCRIPTION	QTY	
TB503D	Toolbox Bracket Driver	1	
TB503P	Toolbox Bracket Passenger	1	
OR			
TB901D	31" Toolbox Bracket Driver	1	
TB901P	31" Toolbox Bracket Passenger	1	
HARDWARE BAG508			
INST008	Installation Instruction	1	
FYZ008	1/2"-20 Nylon Hex Lock Nut	2	
FYZ009	1/2"-13 Hex Nut	2	
FYZ010	1/2" Lock Waser	2	
FYZ011	1/2" Flat Washer	2	
FYZ012	1/2" Flat Washer Large	2	
FYZ014	1/2"-20 x 3.25" Carrige Bolt Grade 8	2	
FYZ016	5/8"-11 Hex Nut	2	
FYZ017	5/8" Lock Washer	2	
FYZ018	5/8" Flat Washer	2	
SBY508S	Stake Pocket Bolt	2	
SF002	2" x 6" Foam Pad	2	


FOR MORE INFORMATION SCAN HERE!



FUNCTION AND STYLE FOR TODAY'S TRUCKS

For each stake pocket bolt (driver and passenger) install 1/2" bolt end of stake pocket bolt through the slot on the truck bed. Install the 1/2" steel washer, lock washer and nut. Leave assembly finger


tight at this stage.



2

Fasten Backrack to the Rail mount bracket, or Toolbox bracket. Finger tighten at this stage.

IMPORTANT
Install the carriage bolt as shown in the diagram with the round head closest to the cab. Failure to do so could result in damage to the cab or rear window.



S/8" STEEL NUT, LOCK WASHER AND FLAT WASHER

KIT #30108

KIT #30108

Fasten Backrack Assembly to the Stake pocket bolt as shown.

Center the Backrack assembly on the truck and final torque all bolts starting with the nuts on the inside of the truck bed, then the rail mount or toolbox bracket and finally the main BACKRACK carriage bolt

