



BLUE OX®

Baseplate Installation Instructions

BX2240 2005 Honda Accord Hybrid No Foglights Installation Instructions

Serial Number

Please read **BOTH** these Installation Instructions and the General Towing Instructions before attempting to install or operate this equipment.

1. Blue Ox® towing products and accessories are intended to be installed by Blue Ox® Dealers who are familiar with our products and have the equipment and knowledge to do “fit work”. When necessary Blue Ox® Dealers can be found at www.blueox.us or by contacting our Customer Care Department at (402) 385-3051.
2. Many Blue Ox® Baseplates are designed to use existing holes and hardware to mount the baseplate to the towed vehicle. Even though bolts are there, do not assume they are adequate for baseplate mounting. Always use hardware supplied in the hardware kit or existing hardware specified in the Baseplate Towing Installation Instructions.

Attachment Tab Height: 15”

Attachment Tab Width: 24”

Bolt Torque Specifications

Torque in Foot-Pounds per Metric Bolts

Bolt Size	Grade 8.8	Grade 10.9
6MM	6	8
8MM	16	22
10MM	31	40
12MM	54	70
14MM	89	117

Confirm the towability and pre-towing procedures for your vehicle with the owner’s manual or contact the vehicle’s manufacturer for specific towing procedures. You can also contact REMCO for additional information at 1(800)228-2481.



Bolt Torque Specifications

Torque in Foot-Pounds per Inch Bolts

Bolt Size	Grade 5	Grade 8
1/4”	10	14
5/16”	19	29
3/8”	33	47
7/16”	54	78
1/2”	78	119
5/8”	154	230

WARNING

Failure to read and follow these instructions could result in separation of the towed vehicle from the tow bar, causing property damage, loss of towed vehicle, personal injury or death.

BX2240 2005 Honda Accord Hybrid No Foglights


Installation Instructions

Parts List

Ref. No.	Qty.	Part #	Description
1	1	61-6166	Weldment, Baseplate, BX2240
2	4	61-5208	Weldment, 3/8"-16 Nutplate, w/ 14" Wire
3	2	201-0443	3/8-16 x 1 Hex Bolt, Grd. 5, ZP
4	6	201-0368	3/8-16 x 1 1/4" Hex Bolt, Grd. 5, ZP
5	8	203-0010	3/8 Lock Washer, ZP
6	4	202-0003	3/8-16 Hex Nut, ZP
7	2	201-0553	1/4-20 x 1/2" Hx. Wshd., Type F Screw
8	2	201-0192	10-32 x 1/2" Slot, Rd. Hd. Screw
9	2	203-0054	#10 Lock Washer
10	2	202-0047	#10-32 Hex Nut
11	2	101-5822	Adapter, 4 Way Connector
12	2	62-3468	Attachment Tab, assembly, SF/SB (R)
	2	226-0046	Baseplate Safety Cable, 36" CL III (Not Shown)
	2	229-0359	Quicklink, 3/8, ZP (Not Shown)
	2	290-0437	Cap Plug, Black (Not Shown)

Tools Required

9/16" Socket	Loctite® RED
Phillips Screw Driver	17MM Socket
Utility Knife	Vise Grip
10MM Socket	13/32" Drill Bit
Tape Measure	12MM Socket



Important:

Use only genuine factory replacement parts on your baseplate. Do **NOT** substitute homemade or non-typical parts. If a bolt is lost or in need of replacement, for your safety and the preservation of your baseplate, be sure to use a replacement bolt of the same grade (In most cases it will be Grade 5, please reference the parts list above). Replacement parts may be ordered through your nearest Blue Ox® Dealer or Distributor.

BX2240

2005 Honda Accord Hybrid

No Foglights

Installation Instructions

Attachment Tabs:


Due to the design of the removable tabs, the RangeFinder II tow bar can not be used. Adapters, except for the BX8833 and BX88151, can not be used with this baseplate.

Instructions:

The front fascia, metal bumper, headlight assemblies and the windshield washer reservoir are removed for the baseplate installation. Drilling is required.

Some vehicles fascias may need trimming. The dimensional variations between otherwise identical vehicles can be considerable. While the baseplate was designed for easy installation, it may be necessary to tailor the baseplate slightly to compensate for auto manufacture's tolerances. These minor adjustments may include filing a hole slightly, bending electrical rods, and/ or bending endplates.


The BX8847 Diode Wiring Kit is recommended for this vehicle.



1. Remove two Phillips push pins from upper, outside edge of the black plastic radiator cover (see grey arrow). Remove regular push pins from radiator (see white arrows) and set cover aside. The driver's side is shown in the photo.



2. Using the 10MM Socket, remove two metric bolts on fascia, just forward of the front tire (see white arrows). Remove one push pin (see grey arrow) and set all aside to be re-installed later. This is done to both sides of the vehicle the driver's side is shown.



3. Remove the four push pins from the front center of the fascia.

BX2240
2005 Honda Accord Hybrid
No Foglights
Installation Instructions




4. On the edge of the fascia, inside the wheel well, there is one Phillips screw to remove. Set these aside to be re-installed later. This is done on both sides of the vehicle, the driver's side is shown. After this is done, you will be able to pull the fascia forward and carefully set it aside.



6. Using a 10MM Socket, remove two bolts from just inside the headlight housing. Set these bolts aside to be re-installed later. This is done on both sides of the vehicle, the driver's side is shown.



5. Remove the metric bolt on the side of the fascia near the headlight assembly using a 10MM Socket. Set bolts aside to be re-installed later. This is done on both sides of the vehicle, the driver's side is shown.



7. Using a 10MM Socket, remove two metric bolts from the top of the headlight assembly. Set bolts aside to be re-installed later. This is done on both sides of the vehicle, the driver's side is shown. Pull the headlight assembly forward and carefully set aside.

BX2240
2005 Honda Accord Hybrid
No Foglights
Installation Instructions



8. Remove two metric bolts from the top of the metal bumper (Photo 8-A) using a 12MM Socket. Remove one metric bolt from the bottom of the metal bumper using a 12MM Socket (Photo 8-B). This is done on both sides of the vehicle, the passenger's side is shown.
9. Straighten the rib on the lower edge of the outside frame rail using the vise grips (See Photo 9-A). This is done to both side of the vehicle, the driver's side is shown. Bend the leading edge of the passenger's side outside frame rail flush with the frame rail (See Photo 9-B).

BX2240


2005 Honda Accord Hybrid

No Foglights

Installation Instructions




10. On the bottom side of the metal bumper, unplug and release the clip holding the temperature sensor to the metal bumper. When this has been disengaged you are able to pull the metal bumper forward and carefully set the metal bumper aside.



12. Measure 1/4" down from the frame rail and clamp baseplate in place using vice grips. The endplate should be flush with the frame rail (See Photo in Step 13).



11. Remove the windshield washer fluid reservoir by removing two metric bolts using a 10MM Socket. Disconnect and plug all hoses. Set the windshield washer fluid reservoir aside to be re-installed later.



13. Using the baseplate as a template, drill the four holes in the side of the frame rail with the 13/32" Drill Bit. This is done to both sides of the vehicle, the driver's side is shown. Make sure there is 1/4" clearance between the baseplate cross tube and the condenser tubing.



BX2240

2005 Honda Accord Hybrid

No Foglights

Installation Instructions


BE SURE TO USE LOCTITE® RED ON ALL BOLTS BEFORE TIGHTENING. TIGHTEN ALL BOLTS ACCORDING TO THE TORQUE CHART ON THE FRONT PAGE OF THESE INSTRUCTIONS OR ON PAGE 3 OF THE BASEPLATE TOWING GENERAL INSTRUCTIONS.



14. Insert the two 3/8-16 nut plates into the frame rail to align with the top two drilled holes on the baseplate and install the 3/8-16 x 1 1/4" hex bolts and 3/8" lock washers (See White Arrows in Photo 14-A). Install the 3/8-16 x 1 1/4" hex bolt, 3/8" lock washer and 3/8-16 hex nut into the center hole. Insert the shorter 3/8-16 x 1" hex bolt, 3/8" lock washer and 3/8-16 hex nut into the lower hole to avoid the air bag sensor (See Grey arrow in Photo 14-A). Tighten all bolts and nut plates. After tightening, cut off the wire on the nut plate (See Photo 14-B).



15. Re-install the metal bumper according to Steps 8-10. Be sure to plug the temperature sensor back in and clip it to the frame rail.



16. Re-install the windshield washer reservoir by replacing the two metric bolts and tightening with the 10MM Socket. You will then need to mark and trim the windshield washer reservoir so that it does **NOT** overlap the baseplate.

Be sure that **ALL** electrical connections are plugged in properly and functioning **BEFORE** Installing the fascia.

BX2240

2005 Honda Accord Hybrid

No Foglights

Installation Instructions

17. Reinstall front fascia according to the instructions on the previous pages (Steps 1-7).
18. Install the tow bar and safety cables according to their instructions. When demonstrating this to the customer, be sure to include all the contents and packages of their Blue Ox products.
19. **DO NOT** substitute other devices if the tow bar pins and clips are misplaced.



CUSTOMER SERVICE COMMITMENT

Blue Ox is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call 1-800-228-9289 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also as a commitment to our customers, should you visit our factory you can stay at our full service Blue Ox campground at no charge along with enjoying a factory tour.

Again thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.



© 2005 Blue Ox
One Mill Road, Industrial Park
Pender, Nebraska 68047
Phone: (402) 385-3051
Fax: (402) 385-3360
www.blueox.us