



BX2301 Installation Instructions 1986-89 Hyundai Excel

1. Read the General Instruction Sheet included with this baseplate.
2. The baseplate mounts to the front underside of the car using eight bolts, four on each side.
3. Remove the two tie down brackets from the vehicle. These are stamped metal plates with an oblong hole that faces downward.
4. Remove the two bolts on each side of the vehicle which attaches the bumper brackets to the vehicle. These bolts are located just above the tie down brackets.
5. Position the lower brackets so that the bracket holes align with the tie down bracket holes. Hand start two of the 10mm bolts and 10mm lock washers. Use Locktite on all bolts and nuts, but do not tighten yet.
6. Position the upper brackets so that the holes in the angle align with the bumper bracket holes. Hand start the remaining 10mm bolts and lock washers.
7. Loosely attach the upper and lower brackets using the 1/2-13 x 1 hex bolts and lock washers.
8. Position the baseplate on the lower brackets and loosely attach using the 1/2-13 x 1 1/2 bolts, nuts and lock washers.
9. When all bolts align, tighten securely.
10. The dimensional variations between otherwise identical cars can be considerable. While the location and size of the holes in the baseplate were designed to allow easy installation, it may be necessary to file a hole slightly to allow a bolt to clear.
11. Install the tow bar and safety cables according to the instructions included in their packages.
12. Do not substitute other devices if the tow bar pin and clip are lost.
13. **DEALERS AND INSTALLERS: BE CERTAIN THE USER RECEIVES THE INSTRUCTION SHEET.**

Automatic

Tools Required

3/4 socket
17mm socket

14mm socket
3/4 open end wrench

Parts List

Ref. No.	Qty.	Part No.	Description
1	1	61-3541	Main Baseplate Assembly
2	2	61-3583	Upper Bracket
3	1	61-3584	Lower Bracket, Driver's Side
4	1	61-3585	Lower Bracket, Passenger's Side
5	4	201-0051	1/2-13 x 1 1/2 Hex Bolt
6	4	201-0060	1/2-13 x 1 Hex Bolt
7	8	201-0423	10mm-1.25 x 35mm Hex Bolt
8	4	202-0005	1/2-13 Hex Nut
9	8	203-0012	1/2 Lock Washer
10	8	203-0104	10mm Lock Washer

