

2000-2005 SATURN L SERIES SEDAN & WAGON

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

Diagram illustrating the assembly of the hitch components, showing the relationship between the hitch, bumper, and trunk pan.

Labels and Callouts:

- 1: Hitch assembly (includes a note: **HITCH WEIGHT: 17 LBS.** and **INSTALL TIME** Professional: 30 MINUTES, Novice (DIY): 60 MINUTES, **INSTALL NOTES:**)
- 2: Washer
- 3: Spacer plate
- 4: Bolt
- 5: Nut
- ATTACHES THROUGH HOLES IN TRUNK PAN
- USE BETWEEN SPACER AND INSIDE THE BUMPER
- USE BETWEEN HITCH AND OUTSIDE BUMPER
- DRILL HOLE THROUGH BUMPER (BOTH SIDES)
- FRONT / REAR orientation indicator
- DESIGNED FOR USE WITH BALLMOUNT D-18 / 45518

- DRILLING REQUIRED

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.