



11453 INSTALLATION INSTRUCTIONS



Safety glasses should be worn at all times while installing this product.

YEARS: 2016-PRESENT

MAKE: NISSAN

MODEL: MICRA

STYLE: HATCHBACK



WARNING: NEVER EXCEED YOUR VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY
For more information log onto www.curtmfg.com & for helpful towing tips log onto www.hitchinfo.com

WEIGHT CARRYING:

TRAILER WEIGHT: 1,000 LBS.

TONGUE WEIGHT: 100 LBS.

WARNING:

WE RECOMMEND THE USE OF 18050 STABILIZING STRAPS FOR ALL NON-TRAILER (WHEEL-LESS) LOADS. PLEASE SEE THE CURT CATALOG OR VISIT US ONLINE AT WWW.CURTMFG.COM FOR FURTHER INFORMATION.

PRO INSTALL TIME: 20 MIN.

NOVICE INSTALL TIME: 40 MIN.

IF YOU ARE HESITANT TO UNDERTAKE THIS TASK ON YOUR OWN, CONTACT AN AUTHORIZED CURT INSTALLER FOR ADDITIONAL ASSISTANCE.




INSTALLATION REQUIRES:

		 11/16" 3/4"
RATCHET	TORQUE WRENCH	SOCKET
		
PANEL REMOVAL TOOL	MASKING TAPE	AVIATION SHEARS
		
SAFETY GLASSES		

INSTALLATION TIPS:

1. BEFORE YOU BEGIN INSTALLATION, READ ALL INSTRUCTIONS THOROUGHLY.
2. TO EASE INSTALLATION, 2 PEOPLE MAY BE REQUIRED.
3. USING PROPER TOOLS WILL GREATLY IMPROVE THE QUALITY OF THE INSTALL AND REDUCE THE TIME REQUIRED.
4. NEED HELP OR HAVE SOME QUESTIONS? CALL TECHNICAL SUPPORT AT 800.798.0813

LEVEL OF DIFFICULTY: EASY


EASY	MODERATE	CHALLENGING
 PART REMOVAL	TEMPORARILY REMOVE UNDERBODY PANEL	
	LOWER EXHAUST	
 TRIM	TRIMMING REQUIRED	

VEHICLE PHOTO:



REPRESENTATIVE PHOTO

HITCH ILLUSTRATION:



MAKE SURE YOUR HITCH MATCHES



SCAN FOR
MORE INFO

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE ALL FASTENERS ARE TIGHT AND ALL STRUCTURAL COMPONENTS ARE SOUND

CURT Manufacturing LLC. warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, CURT Manufacturing LLC. may repair or replace the product at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. CURT Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.


For more information log onto www.curtmfg.com , & for helpful towing tips log onto www.hitchinfo.com

This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York, V.E.S.C.Regulation V-5 and SAE J684.


9/21/2016

INSTALLATION WALKTHROUGH:

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	3	CM-SP16	.250 x 1.50 x 2.00" ROUND HOLE SPACER
2	2	7/16-14 x 1 1/2	CARRIAGE BOLT
3	2	7/16-14	HEX FLANGE NUT
4	1	1/2-13 x 1 3/4, GR8	CARRIAGE BOLT
5	1	HFN 1213, GR8	HEX FLANGE NUT



1. Locate (2) rubber isolator brackets and remove to lower exhaust. On the underbody panel, locate and remove (6) plastic push-pins using the panel removal tool. Remove underbody panel and set aside for later reinstallation.



2. Raise hitch into position using (1) 7/16" bolt and (1) CM-SP16 spacer on each side. Loosely secure using (2) 7/16" hex flange nuts.



INSTALLATION WALKTHROUGH:

3. Secure hitch to the tow loop by using (1) 1/2" bolt, (1) CM-SP16 spacer, and (1) 1/2" hex flange nut. Torque all 7/16" hardware to 59 ft-lbs. and all 1/2" hardware to 110 ft-lbs.



4. On the underbody panel, mark out a 2.375" x 2.25" section centered on the panel using masking tape and trim using aviation shears. Trim off the driver side of the panel from the far most clip using aviation shears. Reinstall following Step 1 in reverse order. **NOTE:** The dimensions are approximate. Confirm fit prior to install.



TOWING SAFETY INFORMATION


Gross Trailer Weight / GTW

The Gross Trailer Weight is the weight of the trailer & cargo. Measure this by putting the fully loaded trailer on a vehicle scale.



Tongue Weight / TW

The downward force that is exerted on the hitch ball by the coupler. The tongue weight will vary depending on where the load is positioned in relationship to the trailer axle(s). To measure the tongue weight, use either a commercial scale or a bathroom scale with the coupler at towing height. When using a bathroom scale with heavier tongue weights, use the method shown and multiply the scale reading by 3.




Weight Carrying / WC

The total weight of both the trailer and the cargo inside. Never exceed the weight capacity of your trailer hitch.

Weight Distribution / WD

Used to balance the weight of the cargo between the front and rear wheels throughout the trailer, allowing for better steering, braking, and level riding.



Sway Control

A device used to reduce the lateral movements of the trailer that are caused by the wind. This works in conjunction with a weight distribution hitch. Do not use this on a class 1 or 2 hitch, or with surge brakes.

How Much Can You Safely Tow?


TRAILER TYPE	TONGUE WEIGHT (lb.)									
	1100	1200	1300	1400	1500	1600				
Coupler										
1100										
1200										
1300										
1400										
1500										
1600										
1700										
1800										
1900										
2000										
2100										
2200										
2300										
2400										
2500										
2600										
2700										
2800										
2900										
3000										
3100										
3200										
3300										
3400										
3500										
3600										
3700										
3800										
3900										
4000										
4100										
4200										
4300										
4400										
4500										
4600										
4700										
4800										
4900										
5000										
5100										
5200										
5300										
5400										
5500										
5600										
5700										
5800										
5900										
6000										
6100										
6200										
6300										
6400										
6500										
6600										
6700										
6800										
6900										
7000										
7100										
7200										
7300										
7400										
7500										
7600										
7700										
7800										
7900										
8000										
8100										
8200										
8300										
8400										
8500										
8600										
8700										
8800										
8900										
9000										
9100										
9200										
9300										
9400										
9500										
9600										
9700										
9800										
9900										
10000										

Refer to owner's manual for towing capabilities and limitations.

Ball Mount

The ball mount is placed inside the opening of the receiver hitch which is mounted to the vehicle. Make sure a hitch pin and clip is properly securing the ball mount to the receiver hitch before you begin towing.

• A: Rise. B: Drop. C: Hole Size. D: Length.



Trailer Ball

The connection from the hitch to the trailer. There are many factors that determine the correct hitch ball:

- Number one is the hitch ball's gross trailer weight rating.
- The mounting platform must be at least 3/8" thick.
- The hole diameter must not be more than 1/16" larger than the threaded shank.
- Every time you tow, check the nut and lock washer to make sure they are fastened securely.

• A: Ball Dia. B: Shank Length. C: Shank Dia. D: Shank Rise.



Coupler

The component that is placed over the trailer ball to connect the vehicle to the trailer. Be sure that the coupler size matches the size of the hitch ball and that the coupler handle is securely fastened. To determine what size hitch ball you need for your application you will need to know the size of coupler that is on the trailer. Be sure your coupler is properly adjusted to the ball you are using.

NOTE: For added security the use of safety devices such as Coupler Safety Pins and Locks is strongly recommended.

Safety Chains

Safety chains are a requirement and should be crossed under the tongue of the trailer so that the tongue will not drop to the road if it becomes separated from the hitch. Always leave enough slack so you can turn. Never allow the safety chains to drag on the ground and never attach the chains to the bumper.

Trailer Classification: Safety Chain Breaking Force - Minimum

Class 1: 2,000 lbs. (8.9 kN)

Class 2: 3,500 lbs. (15.6 kN)

Class 3: 5,000 lbs. (22.2 kN)

The strength rating of each length of safety chain or its equivalent and its attachments shall be equal to or exceed in minimum breaking force the GVWR (Gross Vehicle Weight Rating) of the trailer.

Electrical

Trailer lights, Electric Brakes, Break-away systems - Every time you tow, be sure to check that all components are working properly.

Wiring identification by color:

4-WAY				5-WAY			6-WAY		7-WAY	
GREEN	YELLOW	BROWN	WHITE	RED	BLUE	PURPLE				
RIGHT TURN & BRAKE	LEFT TURN & BRAKE	TAILLIGHTS	GROUND	AUXILIARY POWER	ELECTRIC BRAKES	BACK-UP LIGHTS				

CURT DISCLAIMER: WIRING COLOR SHOWN WORK IN CONJUNCTION WITH CURT MANUFACTURING PRODUCTS.

11453

9/21/2016

NISSAN MICRA

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 1,000 LBS. TRAILER WEIGHT & 100 LBS. TONGUE WEIGHT.

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY 18050 STABILIZING STRAPS.





WARNING: ** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY **

WARNING: *** DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY ***

FOR MORE INFORMATION LOG ONTO WWW.CURTMFG.COM & FOR HELPFUL TOWING TIPS LOG ONTO WWW.HITCHINFO.COM
HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813



Parts List				
ITEM	QTY	PART NUMBER	DESCRIPTION	
1	3	CM-SP16	.250 x 1.50 x 2.00" ROUND HOLE SPACER	
2	2	7/16-14 x 1 1/2	CARRIAGE BOLT	
3	2	7/16-14	HEX FLANGE NUT	
4	1	1/2-13 x 1 3/4, GR8	CARRIAGE BOLT	
5	1	HFN 1213, GR8	HEX FLANGE NUT	



TOOLS REQUIRED
RATCHET
TORQUE WRENCH
11/16", 3/4" SOCKETS
PANEL REMOVAL TOOL
MASKING TAPE
AVIATION SHEARS
SAFETY GLASSES

HITCH WEIGHT: 13 LBS.
INSTALL TIME
PROFESSIONAL: 20 MINUTES
NOVICE (DIY): 40 MINUTES
INSTALL NOTES:
-TEMPORARILY REMOVE UNDERBODY PANEL
-LOWER EXHAUST
-TRIMMING REQUIRED



INSTALLATION STEPS

1. Locate (2) rubber isolator brackets and remove to lower exhaust. On the underbody panel, locate and remove (6) plastic push-pins using the panel removal tool. Remove underbody panel and set aside for later reinstallation.
2. Raise hitch into position using (1) 7/16" bolt and (1) CM-SP16 spacer on each side. Loosely secure using (2) 7/16" hex flange nuts.
3. Secure hitch to the tow loop by using (1) 1/2" bolt, (1) CM-SP16 spacer, and (1) 1/2" hex flange nut. Torque all 7/16" hardware to 59 ft-lbs. and all 1/2" hardware to 110 ft-lbs.
4. On the underbody panel, mark out a 2.375" x 2.25" section centered on the panel using masking tape and trim using aviation shears. Trim off the driver side of the panel from the far most clip using aviation shears. Reinstall following Step 1 in reverse order. **NOTE:** The dimensions are approximate. Confirm fit prior to install.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.



Scan for more information

CURT Manufacturing LLC., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, CURT Manufacturing LLC., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. CURT Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York, V.E.S.C.Regulation V-5 and SAE J684.