



Truck and Jeep Accessories

1999-2007 FORD F250, F350, SUPER DUTY BODY MOUNT STEEL KIT KF04059ST



www.Daystarweb.com

Tech Support Contact Info Tech@DaystarWeb.com

Phone: 623-907-0081

Fax: 623-907-0088

841 South 71st Avenue, Phoenix, AZ 85043

Introduction

Daystar® is your number one source for Made in the USA quality vehicle accessories, backed by our exclusive *Go Everywhere*® Limited Lifetime Warranty (see terms at Daystarweb.com). To ensure your safety and proper installation of this product, take a moment to read all instructions and product safety information before trying to install your Daystar® product. If you have any technical questions after reading these instructions, we are here to help. Contact us at 800-595-7659.

Product Safety Information

Throughout these instructions, important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words are as follows:



WARNING

A hazardous situation which, if not avoided, could result in death or serious injury. You can be seriously injured or killed if you don't follow instructions.



CAUTION

A hazardous situation which, if not avoided, could result in minor or moderate injury. You can be moderately injured and also may suffer property damage if you don't follow instructions.

Notice

Careful attention is required to this instruction or operation, but this does not generally relate to personal injury. Damage to your product or other property may result if you don't follow instructions.



Bill of Materials		
Part #	Description	Quantity
S22318	Threaded Steel Mount	8
S22319	Large Steel Mount	8
S10126	Washer	2

Installation Instructions

This kit is meant to be used in conjunction with Daystar body mount kit KJ04050BK/KJ04050KV. Use the steel components provided in this kit when following the installation instructions of the body mount kit.

Install *kit body mounts* on *kit steel mounts*, Assemble the kit components as shown. See figures 1 through 6.

Fig 1



Fig 2



Fig 3



Fig 4



Fig 5



Fig 6



Notice

Verify that all parts are installed properly, all fasteners are torqued to factory specification, all lines, hoses, and wiring are not stretched or pinched. Retighten all bolts after 500 miles again to factory specifications.