

SAFETY

Your safety and the safety of others is very important.

- In order to help you make informed decisions about safety, we have provided installation instructions and other information.
- These instructions alert you to potential hazards that could hurt you or others.
- Please do a job safety analysis (JSA) before each task to identify potential hazards for your situation and remove/protect against them.
- You must use your own good judgment, and take your time.

Read and understand all safety precautions and instructions before installing this product.

THIS PRODUCT IS FOR OFFROAD USE ONLY. ALL LIABILITY FOR INSTALLATION AND USE RESTS WITH THE OWNER.

CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE.

Injury hazard

Failure to observe these instructions could lead to severe injury or death.

- Always remove jewelry and wear eye protection.
- Always use appropriate and adequate care in lifting components into place.
- Always insure components will remain secure during installation and operation.
- Always wear safety glasses when installing this kit
- Always use extreme caution when cutting and trimming during fitting.
- Always tighten all nuts and bolts securely per installation instructions.
- □ Always perform regular inspections and maintenance on mounts and related hardware.





Overview

Congratulations on your new purchase of the Fab Fours Tube Doors!

Your Tube Doors were designed in 3-D from digitized data, CNC laser cut, fabricated, and powder coated... all in the U.S.A. Enjoy the fit and finish of JK tube doors from Fab Fours, Inc.

WARNING: This product was designed to be used with the 18-20 Jeep Wrangler JL ONLY.

NOTICE: Some minor door striker plate adjustment maybe needed for proper door closure.





Installation Instructions JL TUBE DOORS Product Number: JL1030

2018-2020 Jeep JL

I. Tools Required

- 3/16" Allen Wrench
- Open End Wrench
- Torx socked
- Socket Set and Ratchets

II. Factory OEM Door Removal

1. Remove both OEM door locking nuts using a T50 torx driver








Installation Instructions JL TUBE DOORS Product Number: II 1030

Product Number: JL1030 2018-2020 Jeep JL

2. Remove the door restraining strap webbing by separating the nylon loop from the metal hook.



3. Disconnect the door power window and lock wiring harness if applicable.





Installation Instructions JL TUBE DOORS Product Numbers II 1020

Product Number: JL1030 2018-2020 Jeep JL

4. Remove the door dente using a T40 torx



5. With the assistance of a friend, open the door 45° and lift it off of the factory hinges.





III. Fab Four Tube Door Installation

1. Install and loosely tighten the hinges using the provided flat head bolts, washers, and nuts. Install and tighten mirror bracket on the doors using the provided button head bolts washers and nuts.







2. Install and fully tighten the latches and latch spacers using the included button head bolts, washers, and nuts.

Note: The latch spacers go between the latch and the door skin, pictured below. Latches mount to the back of the door.









Figure1: front door latch orientation



Copyright 2009 Fab Fours, Inc. Page 8 of 13 JL1030_Installation_Manual_REV_A



3. Install and fully tighten the limiting strap to inside of door using the provided flat head socket screws, washers and nuts.







Installation Instructions JL TUBE DOORS Product Number: JL1030

1uct Number: JL1030 2018-2020 Jeep JL

4. Cut and install the rubber door seal to the inside edge of the door. Both front and rear seals measure 11 ½ inches.





Copyright 2009 Fab Fours, Inc. Page 10 of 13 JL1030_Installation_Manual_REV_A



Installation Instructions JL TUBE DOORS

Product Number: JL1030 2018-2020 Jeep JL

5. Lift your new Fab Fours tube door onto the factory hinges and latch the door closed. Fully tighten all hardware.

Note: It's recommended that someone lift up on the rear of the closed door while tightening the hinge bolts to add preload to the assembly.





Copyright 2009 Fab Fours, Inc. Page 11 of 13 JL1030_Installation_Manual_REV_A



Installation Instructions JL TUBE DOORS

Product Number: JL1030 2018-2020 Jeep JL

6. Adjustments to the striker plates may be required. If needed, tool required for adjustment is included with OEM Jeep tool kit.

Note: Loosen two star screws and slide towards outside of the jeep so the latch on the tube door catches. This is not necessary to do if the door shuts with no issues.



7. If Fab Fours Mirror brackets (JK1032-1) were purchased, install the mirror using the provided button head bolt.





Installation Instructions JL TUBE DOORS Product Number: JL1030

2018-2020 Jeep JL

IV. Maintenance/Care

- □ Periodically check and tighten all nuts.
- □ Stripped, fractured, or bent bolts or nuts need to be replaced.

V. Contact Information

Fab Fours Inc.Phone(866)-385-19052213 Industrial Park RdFax(970)-385-1914Lancaster, SC 29720EmailSupport@fabfours.com



More than expected... Better than expected.



Copyright 2009 Fab Fours, Inc. Page 13 of 13 JL1030_Installation_Manual_REV_A