

SEAT COVERS  
BY



## SUPER-GRIP® THE SLIP RESISTANT FASTENING SYSTEM

### INSTALLATION INSTRUCTIONS FOR

NP92-66/ Oe32-66/ SL62-66/ SP82-66/ TR42-66/ TRS42-66

#### CUSHION COVERS

1. Center cover on seat
2. Lift cushion to halfway up position and pass back flap through crevice
3. With cushion in up position locate straps and buckle to back flap
4. smooth out cover and adjust straps to equalize tension for a better fit

#### BACKREST COVER


1. Remove headrests, (see note below)
2. Place cover over backrest. Ensure cover is installed under seat belt strap
3. Ensure openings for headrest posts are tucked under headrest base to reduce cover movement during installation.
4. Pass side velcro behind the seat and attach to the bottom of cover
5. **DRIVERS SIDE.** Pass center strap through opening on metal seat belt base on floor and buckle
6. **PASSENGER SIDE.** Anchor each center strap on metal seat belt base on the floor and buckle
7. Install adhesive back velcro (included) on inside edge of armrest well to align with velcro on seat cover. (see note below)
8. Secure top portion of backrest by placing adhesive velcro supplied on flat surface behind the seat. (see note below)
9. Smooth out cover and adjust straps/velcro to equalize tension for a better fit.

#### D) ARMREST COVER

- 1) Fold down armrest
- 2) Slip cover over armrest and attach velcro
- 3) Position adhesive Velcro supplied to align with Velcro on cover around the edge of cup holder and on top. (see note below)


#### NOTES:

##### 1) SELF-LOCKING SUPER-GRIP® BUCKLE:



##### 2) HEAD REST REMOVAL:

Push in side release buttons  
- Lift off  
(If unable to remove consult dealership)



##### 3) RE-INSTALLATION OF HEADRESTS

- A) Ensure pre-cut holes in seat cover align with holes in headrest base.
- B) Replace headrests

##### 4) ADHESIVE BACK VELCRO

Before positioning velcro, clean area with alcohol swab provided.

**WARNING: SEATS WITH INTEGRATED SEAT AIRBAGS MUST BE COVERED ONLY WITH SEATCOVERS DESIGNED WITH OPENINGS THAT WILL NOT INTERFERE WITH THE DEPLOYMENT OF THE AIRBAG. NEVER INSTALL SEAT COVERS WITHOUT THESE OPENINGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS AND COULD RESULT IN SERIOUS INJURY.**



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438  
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com