

If you have any comments or concerns,  
please feel free to contact our  
customer service department at:  
Toll-free: 1-800-835-0438  
OR  
Email: info@gofia.com

SEAT COVERS  
BY

*fia*  
The Leader in Custom Fit


FEATURING

**SUPER-GRIP®**

**THE SLIP RESISTANT FASTENING SYSTEM**

INSTALLATION INSTRUCTIONS  
FOR

Oe37-63/ SL67-63/ SP87-63/ TR47-63



Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

**INSTRUCTIONS:**

**A) BACKREST COVERS X 2:**

- 1) Move seat to most forward position
- 2) Pull cover down firmly
- 3) Tuck flap through crevice and attach to velcro at back

**B) CUSHION COVER - "60" PORTION:**

- 1) For seat with cup holder (see NOTE)
- 2) Position cover over driver cushion
- 3) Pass the front straps under seat. Buckle to back flap
- 4) Pass side straps through the opening between the molded plastic and the seat. Buckle to back flap
- 5) Secure velcro to carpet on seat
- 6) Adjust all straps, buckles and velcro to equalize tension

**C) CUSHION COVER - "40" PORTION:**

- 1) Position cover over passenger cushion
- 2) Pass the front strap under seat. Buckle to back flap
- 3) Pass side straps through the opening between the molded plastic and the seat. Buckle to back flap
- 4) Adjust straps and buckles to equalize tension

**D) ARMREST / STORAGE COMPARTMENT:**


- 1) Open armrest / storage compartment
- 2) Center cover under armrest
- 3) Position adhesive backed velcro (supplied) inside the console to align with the velcro on cover. **NOTE: BEFORE POSITIONING VELCRO, CLEAN AREA WITH ALCOHOL SWAB PROVIDED**

**E) ARMREST LID**

- 1) Open armrest / storage compartment
- 2) Slide cover over lid
- 3) Adjust cover to go over back and front edge of lid

**NOTES:**

**1) SELF-LOCKING SUPER-GRIP® BUCKLE:**



**2) CUP HOLDER**

- Slide cup holder up to release from bolts
- After the seat cover has been installed, locate the bolts through the stretch fabric and make one slit for each bolt just large enough to allow the bolt to come through (THE STRETCH FABRIC WILL NOT RUN)
- Re-install cup holder

**WARNING: SEATS WITH INTEGRATED SEAT AIRBAGS MUST BE COVERED ONLY WITH SEATCOVERS DESIGNED WITH OPENINGS THAT WILL NOT INTERFERE WITH THE DEPLOYMENT OF THE AIRBAG.. NEVER INSTALL SEAT COVERS WITHOUT THESE OPENINGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS AND COULD RESULT IN SERIOUS INJURY.**

*fia*

Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438  
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com

7-23-13