

If you have any comments or concerns,  
please feel free to contact our  
customer service department at:  
Toll-free: 1-800-835-0438  
OR  
Email: info@gofia.com

SEAT COVERS  
BY

*fia*  
The Leader in Custom Fit

FEATURING

**SUPER-GRIP®**

**THE SLIP RESISTANT FASTENING SYSTEM  
INSTALLATION INSTRUCTIONS**

FOR

NP97-81/ Oe37-81/ SL67-81/ SP87-81/ TR47-81/ TRS47-81




Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

**INSTRUCTIONS:**

- A) BACKREST COVER – “40” PORTION X 2:**
- 1) Remove head rest (see note)
  - 2) Open zipper
  - 3) Slip cover over backrest under seat belt
  - 4) Close zipper (see note)
  - 5) Tuck flaps under backrest and attach to Velcro at back
  - 6) Adjust Velcro to equalize tension
  - 7) Replace headrests (see note)
- B) CUSHION COVER - “40” PORTION X 2:**
- 1) Center cover on the seat
  - 2) Pass the front strap under seat and buckle to back flap
  - 3) Pass side straps around back of seat and buckle
  - 4) Adjust straps and buckles to equalize tension
- C) CUSHION COVER – CENTER “20” PORTION X 1:**
- 1) Repeat “B)”
- D) BACKREST COVER – CENTER “20” PORTION X 1**
- 1) Follow steps 1-3 in “D)”
  - 2) Snug cover at back of console so the Velcro on the cover is positioned through the crevice where the lid and console are hinged
  - 3) secure adhesive Velcro on the inside back of console and attach.
- NOTE: BEFORE POSITIONING VELCRO, CLEAN AREA WITH ALCOHOL SWAB PROVIDED**

**NOTES:**

**1) SELF-LOCKING SUPER-GRIP® BUCKLE:**




**2) HEAD REST REMOVAL:**

- A) - Insert paper clip into holes at base to release  
- Lift off

**OR**

- B) - Push in side release buttons  
- Lift off

(If unable to remove consult dealership)



**3) SEATS WITH SIDE ARMRESTS:**

- Locate opening in stretch fabric
- Slip armrest through opening

**4) ZIPPERS:**

- For ease in installation the zipper is longer than the cover.
- Tuck excess zipper under cover

**5) RE-INSTALLATION OF HEADRESTS**

- Locate headrest base and put a small slit in the stretch fabric to accommodate each of the posts
- Stretch fabric will not run
- Replace headrests

**WARNING: SEATS WITH INTEGRATED SEAT AIRBAGS MUST BE COVERED ONLY WITH SEATCOVERS DESIGNED WITH OPENINGS THAT WILL NOT INTERFERE WITH THE DEPLOYMENT OF THE AIRBAG.. NEVER INSTALL SEAT COVERS WITHOUT THESE OPENINGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS AND COULD RESULT IN SERIOUS INJURY.**

*fia*

Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438  
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com

7-23-13