

MBRP Muffler Installation Instructions22710172009-2011Z1 Turbo

Note: Local regulations may limit or prohibit modification to your snowmobile's emissions system and/or the sound levels that it generates. It is your responsibility to be aware of restrictions that may apply to your intended use of this product.

- Remove the springs and the mounting bracket securing the stock muffler. (Place these springs and the bracket safely aside so that they can be reused.)
 Pictured to the right is the bracket that must be removed for the installation of the MBRP muffler.
- 2. Remove the stock muffler from the belly pan.
- 3. Using the provided heat tape wrap the main oil line (pictured) for added protection.



- 4. Install the MBRP muffler in the same location as the original equipment, using the stock springs and the bracket to secure it in all provided locations. Use the provided 8mm bolt and washers to properly space the stock bracket from the MBRP muffler.
- 5. Tighten all of the fasteners and ensure the springs are securely mounted.

NOTE: To avoid exhaust leaks use a high heat silicone to seal all connections between the expansion chambers and the muffler. Monitor the exhaust for leaks during the first 200 miles after your installation and re-apply silicone where necessary. We suggest having your local snowmobile mechanic or performance shop install this product.

CAUTION: **<u>DO NOT</u>** touch the muffler while the snowmobile is running or shortly after it has run, as it may result in personal injury.

MBRP Ltd. warranty applies for a two (2) year period from the date of purchase to defects in product material and workmanship and is to the original purchaser on record and for the original vehicle for which it was designed and installed. This warranty is limited, at MBRP Ltd. sole determination, to the repair or replacement of defective product only and does not include the cost of removal or re-installation, damage by accident, abuse, misuse or misapplication or any consequential damages however they may arise. Determination of warranty coverage shall be at the discretion of an authorized MBRP Ltd. quality engineer.