

MBRP Muffler Installation Instructions309T209'08-'14Yamaha Nytro

Note: Local regulations may limit or prohibit modification to your snowmobile's emissions system and/or the sound levels that it generates. It is your responsibility to be aware of restrictions that may apply to your intended use of this product.

- 1. Remove the side cover 10mm bolts (2) and the plastic clips (2), slide the panels forward and lift off of the machine.
- 2. Remove the seat fastening 12mm bolts (2), one on each side. Lift the seat off of the tunnel.
- 3. Remove the 5mm Allen bolts (3) that attach the rear plastic cover over the muffler. Remove the cover.
- 4. Using a 5mm Allen wrench remove the rear muffler mount.
- 5. Remove the rubber grommets (3) to access the muffler, remove the front muffler mount bolts and loosen the center front most bolt. (Center hole.)
- 6. Remove the stock muffler from the sled. Keep the stock clamps and the gasket for reuse.
- 7. Install the stock exhaust gasket on the MBRP muffler and install one of the front mounting rubber grommets from the stock muffler on to the MBRP muffler's front mount.
- 8. Install the MBRP muffler onto the stock exhaust pipe.
- 9. Mount the MBRP muffler with the front most bolt and replace the rubber grommets (3).
- 10. Complete the installation by carefully working backwards through steps 1-5.



NOTE: To avoid exhaust leaks use high heat silicone to seal all of the connections between expansion chambers and the muffler. Monitor for leaks during the first 200 miles after your installation and re-apply silicone where it is necessary. We suggest having your local snowmobile mechanic or performance shop install this product.

CAUTION: **<u>DO NOT</u>** touch muffler while snowmobile is running or shortly after it has run, as it may result in personal injury.

MBRP Ltd. warranty applies for a two (2) year period from the date of purchase to defects in product material and workmanship and is to the original purchaser on record and for the original vehicle for which it was designed and installed. This warranty is limited, at MBRP Ltd.'s sole determination, to the repair or replacement of defective product only and does not include the cost of removal or re-installation, damage by accident, abuse, misuse or misapplication or any consequential damages however they may arise. Determination of warranty coverage shall be at the discretion of an authorized MBRP Ltd. quality engineer.