

Rampage Front Custom Fit Neoprene Seat Covers for Jeep Wrangler 2door and 4-door 2007+

PARTS LIST

- 1 left side top cover
- 1 Right side top cover

- 1 Right side bottom cover
- 2 Headrest covers

1 Left side bottom cover

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY.
- 2. Remove headrests from seats.
- 3. Separate and identify the left and right side (driver and passenger) components. There is a pocket on the side of the lower seat cover that should face towards the outside of the vehicle. Use this to identify the correct cover. There is a flap for the Airbag system on the outside of the top half covers. Use these to identify the correct cover.
- 4. Pull the top cover over the seat and into place. Pull the flap at the lower front through the split between the upper and lower portion of the seat. Attach to the rear portion of the cover with the Velcro on the flap.
- 5. Pull the lower seat cover over the lower seat section. Run the long straps under the seat towards the back. NOTE: Be sure the straps are loosened to make installation easier. Now insert the clip from the strap into the receiver on the rear section.
- 6. Tighten the straps until snug on the seat. Pull the side straps under the seat and secure them under tension to the seat frame.
- 7. Install the headrest cover by pulling over the headrest and wrapping the cover under. Secure with the Velcro on the flaps.
- 8. Repeat for other side.
- 9. <u>IMPORTANT: To re-install the headrests it is necessary to puncture a hole for the posts.</u> Use a scissor or screwdriver to puncture a hole in the seat cover at the proper locations.