



www.skyjacker.com

1966 - 1977 Ford Bronco
0" - 7" Lift
Adjustable Front Track Bar
Installation Instructions

REQUIRED TOOL LIST:



- Safety Glasses
- Metric / Standard Wrenches & Sockets
- Lithium Grease
- Tape Measure
- Torque Wrench

Before beginning the installation, thoroughly & completely read these instructions & the enclosed driver's WARNING NOTICE. Affix the WARNING decal in the passenger compartment in clear view of all occupants. Please refer to the Parts List to insure that all parts & hardware are received prior to the disassembly of the vehicle. If any parts are found to be missing, contact SKYJACKER® Customer Service at 318-388-0816 to obtain the needed items. If you have any questions or reservations about installing this product, call SKYJACKER® Technical Assistance at 318-388-0816.

Component Box Breakdown:

Part #: FTBA67

Item #	Description	Qty
FTBA67-B	FRONT ADJUST TRACK BAR	1
FTBA67-RE	FRONT TRACK BAR ROD END	1
ES3498S	ES3498S TURN BUCKLE	1

Item #	Description	Qty
HB-FTBA67	HDWR BG: FTBA67 TRACK BAR	1
I-FTBA67	INST SHEET: FTBA67	1

Hardware Bag Breakdown:


Part # HB-FTBA67

Item #	Description	Qty
2501	TRACK BAR BUSHING / 1.00 ID	2
2502	TRACK BAR BUSHING / .750 ID	2
GMCL	CRUSH SLEEVE / .625 ID	1

Item #	Description	Qty
TS01	CRUSH SLEEVE / .750 ID	1
TS02	CRUSH SLEEVE / .563 ID	1

Installation:

1. With the vehicle on flat level ground, set the emergency brake, & block the front & rear tires / wheels.
2. Remove the OEM front track bar using a 15/16" & 1 1/8" socket / wrench. **Note:** If needed, attach a ratchet strap between the frame & the front differential to take the load off of the OEM front track bar.
3. Install the supplied 3/4" ID bushings & 3/4" OD sleeve into the eyelet of the new Skyjacker front adjustable track bar using a light coat of lithium grease applied to each component. **Note:** The supplied 9/16" ID sleeve is to be used on 1966 - 1975 Ford Bronco models & the supplied 5/8" ID sleeve is to be used on 1976 - 1977 Ford Bronco models.
4. Install the supplied 1" ID bushings & 1" OD sleeve into the eyelet of the new Skyjacker front adjustable track bar rod end using a light coat of lithium grease applied to each component.
5. Using a tape measure, check the front of the vehicle to make sure the body is centered over the front tires / wheels & adjust the new Skyjacker front track bar by adjusting the new Skyjacker turn buckle inward or outward to align the new front adjustable track bar with the upper & lower mounting locations.
6. Install the new Skyjacker front adjustable track bar with the eyelet of the new front adjustable track bar at the upper frame mounting location & the eyelet of the new front adjustable track bar rod end at the lower axle mounting location using the OEM hardware, a 15/16", & 1 1/8" socket / wrench. (See Photos # 1 & # 2)
7. Position the new Skyjacker turn buckle clamps so there is clearance during complete suspension travel & tighten using a 24mm socket / wrench. (See Photo # 3)



Final Notes:

- After the installation is complete, double check that all nuts & bolts are tight. Refer to the following chart below for the proper torque specifications.
- With the vehicle placed on the ground, cycle the steering lock to lock & inspect the steering, suspension, brake lines, front & rear drivelines, fuel lines, & wiring harnesses for proper operation, tightness, & adequate clearance.
- After the first 100 miles, check all of the hardware for the proper torque & periodically thereafter.

<u>TORQUE SPECIFICATIONS</u>					
<u>INCH SYSTEM</u>			<u>METRIC SYSTEM</u>		
Bolt Size	Grade 5	Grade 8	Bolt Size	Class 8.8	Class 10.9
5/16	15 FT LB	20 FT LB	6MM	5 FT LB	9 FT LB
3/8	30 FT LB	35 FT LB	8MM	18 FT LB	23 FT LB
7/16	45 FT LB	60 FT LB	10MM	32 FT LB	45 FT LB
1/2	65 FT LB	90 FT LB	12MM	55 FT LB	75 FT LB
9/16	95 FT LB	130 FT LB	14MM	85 FT LB	120 FT LB
5/8	135 FT LB	175 FT LB	16MM	130 FT LB	165 FT LB
3/4	185 FT LB	280 FT LB	18MM	170 FT LB	240 FT LB

- The above specifications are not to be used when the bolt is being installed with a bushing.

Seat Belts Save Lives, Please Wear Your Seat Belt.



**Jesus Forgives,
Rocks Don't**

Jesus Christ Died For You.

John 3:16

For God so loved the world that He gave His only Son, so that everyone who believes in Him should not perish, but have everlasting life.
Romans 3:23

For all have sinned; all fall short of God's glorious standard.
Ephesians 2:8

God saved you by his special favor when you believed. And you can't take credit for this; it is a gift from God.
Psalms 18:2

The Lord is my Rock, my fortress, and my savior; my God is my Rock, in whom I find protection. He is my shield, the strength of my salvation, and my stronghold.
Romans 10:9-10

That if you shall confess with thy mouth the Lord Jesus, and shall believe in your heart that God hath raised him from the dead, you shall be saved. For with the heart man believeth unto righteousness; and with the mouth confession is made unto salvation.

Pray This Simple Prayer:

God, I come to You admitting I have sinned against You and I need you to take control of my life. The Bible says anyone who calls on the name of the Lord will be saved. I am calling on You, Jesus. I ask that You come live in my heart and be the Lord over my life today. I do believe You died on the cross for me and came back to life to give me life! Thank You, Lord Jesus for a new life in You!

Now, go and tell somebody about your new life in Jesus, get a Bible, begin to read it, and go to a Bible believing church.

If you would like someone to pray with you, call Kenneth Copeland Ministries anytime at 800-600-7395.

To listen to commercial free Christian radio on the web, go to www.887fm.org

Jesús murió por ti.

Juan 3:16

“Porque tanto amó Dios al mundo, que dio a su Hijo unigénito, para que todo el que cree en él no se pierda, sino que tenga vida eterna.”
Romanos 3:23

“Pues todos han pecado y están privados de la gloria de Dios.”
Efesios 2:8

“Porque por gracia ustedes han sido salvados mediante la fe; esto no procede de ustedes, sino que es el regalo de Dios.”
Salmos 18:2

“El Señor es mi roca, mi amparo, mi libertador; es mi Dios, el peñasco en que me refugio. Es mi escudo, el poder que me salva, ¡mi más alto escondite!”
Romanos 10:9-10

“9 Que si confi esas con tu boca que Jesús es el Señor, y crees en tu corazón que Dios lo levantó de entre los muertos, serás salvo. 10 Porque con el corazón se cree para ser justificado, pero con la boca se confi esa para ser salvo.”

Ahora dí esta simple oración:

Dios, vengo a Ti y admito que he pecado contra Ti, necesito que tomes el control de mi vida. La Biblia dice que todo aquel que invoca el nombre del Señor escapará con vida. En este momento yo clamo ante Ti, Jesús; te pido que vengas a vivir en mi corazón y que tomes el control de mi vida. ¡Yo creo que tu moriste en la cruz y resucitaste para darme vida! ¡Gracias Señor Jesús, por una nueva vida que tengo en Ti! Amen.

Ahora ve y dile a alguien sobre la nueva vida que tienes en Cristo. Compra una Biblia y empieza a leerla. Busca una Iglesia que cree en la Biblia y hazte parte de esa Iglesia.

Si te gustaría orar con alguien, puedes llamar a este número 800-600-7395

Puedes ir a este sitio de Internet para escuchar música Cristiana sin anuncios, www.887fm.org

Check out our favorite ministries at:

www.innministries.org

www.familychurch.org

www.kcm.org

