

- 1 Hold the hood protector to the hood and familiarize yourself with the fit.
- 2 Cut out template at bottom of this page.
- 3 Use a pencil to create a hole through the template at the "rubber bump-on location".
- 4 Locate the area near the front corners of the hood where the template fits and clean the area with the alcohol pad provided. Secure the template in place with tape.
- 5 With a #2 pencil make a mark on the hood through the hole in the template. Remove the template and place rubber bump-on on the pencil mark. Flip the template and repeat for the other side of the hood.
- 6 Open the hood and remove the 4 clips holding the rubber seal in place on the underside of the hood. (fig. 1)
Position the Hood Protector in place by sliding the mounting tabs behind the rubber seal, lining up the mounting holes with the holes in the hood.
- 7 Using the screws and washers provided attach the rubber seal and hood protector to the hood. (fig. 2)

KIT CONTAINS:
HOOD PROTECTOR
4 WASHERS
4 SCREWS
2 BUMPERS
1 ALCOHOL PAD
TOOLS NEEDED:
PHILLIPS SCREWDRIVER
PENCIL
MASKING TAPE

CLEANING: USE ONLY SOAPY WATER AND A SOFT CLOTH. NEVER USE PAPER TOWELS, PETROLEUM PRODUCTS OR SOLVENTS TO CLEAN YOUR HOOD PROTECTOR.

