

- 1 Hold the hood protector in place and familiarize yourself with the fit. Lift the hood and remove any dirt or debris.
- 2 Remove the clips that attach the rubber seal to the hood where hood protector will be mounted.
- 3 Position the hood protector in place by sliding the mounting tabs of the hood protector behind the rubber seal, lining up the holes in the mounting tabs with the holes in the hood. Using the screws with flat washers, attach the hood protector to the hood. Tighten just enough to hold the hood protector in place.
- 4 Close the hood **CAREFULLY** to check the fit. If the hood protector is not centered, slightly loosen the screws and move it to one side or the other until it is centered. When you are satisfied the hood protector is in place, tighten the screws until snug. **DO NOT OVER TIGHTEN this may damage your new hood protector.**

CLEANING: USE ONLY SOAPY WATER AND A SOFT CLOTH. NEVER USE PAPER TOWELS, PETROLEUM PRODUCTS OR SOLVENTS TO CLEAN YOUR HOOD PROTECTOR.

Stampede Automotive Products • Visit us at stampedeproducts.com • 800-241-7219

KIT CONTAINS:
HOOD PROTECTOR
6 WASHERS
6 SCREWS
TOOLS NEEDED:
PHILLIPS
SCREWDRIVER

- 1 Hold the hood protector in place and familiarize yourself with the fit. Lift the hood and remove any dirt or debris.
- 2 Remove the clips that attach the rubber seal to the hood where hood protector will be mounted.
- 3 Position the hood protector in place by sliding the mounting tabs of the hood protector behind the rubber seal, lining up the holes in the mounting tabs with the holes in the hood. Using the screws with flat washers, attach the hood protector to the hood. Tighten just enough to hold the hood protector in place.
- 4 Close the hood **CAREFULLY** to check the fit. If the hood protector is not centered, slightly loosen the screws and move it to one side or the other until it is centered. When you are satisfied the hood protector is in place, tighten the screws until snug. **DO NOT OVER TIGHTEN this may damage your new hood protector.**

CLEANING: USE ONLY SOAPY WATER AND A SOFT CLOTH. NEVER USE PAPER TOWELS, PETROLEUM PRODUCTS OR SOLVENTS TO CLEAN YOUR HOOD PROTECTOR.

Stampede Automotive Products • Visit us at stampedeproducts.com • 800-241-7219

KIT CONTAINS:
HOOD PROTECTOR
6 WASHERS
6 SCREWS
TOOLS NEEDED:
PHILLIPS
SCREWDRIVER

- 1 Hold the hood protector in place and familiarize yourself with the fit. Lift the hood and remove any dirt or debris.
- 2 Remove the clips that attach the rubber seal to the hood where hood protector will be mounted.
- 3 Position the hood protector in place by sliding the mounting tabs of the hood protector behind the rubber seal, lining up the holes in the mounting tabs with the holes in the hood. Using the screws with flat washers, attach the hood protector to the hood. Tighten just enough to hold the hood protector in place.
- 4 Close the hood **CAREFULLY** to check the fit. If the hood protector is not centered, slightly loosen the screws and move it to one side or the other until it is centered. When you are satisfied the hood protector is in place, tighten the screws until snug. **DO NOT OVER TIGHTEN this may damage your new hood protector.**

CLEANING: USE ONLY SOAPY WATER AND A SOFT CLOTH. NEVER USE PAPER TOWELS, PETROLEUM PRODUCTS OR SOLVENTS TO CLEAN YOUR HOOD PROTECTOR.

Stampede Automotive Products • Visit us at stampedeproducts.com • 800-241-7219

KIT CONTAINS:
HOOD PROTECTOR
6 WASHERS
6 SCREWS
TOOLS NEEDED:
PHILLIPS
SCREWDRIVER

- 1 Hold the hood protector in place and familiarize yourself with the fit. Lift the hood and remove any dirt or debris.
- 2 Remove the clips that attach the rubber seal to the hood where hood protector will be mounted.
- 3 Position the hood protector in place by sliding the mounting tabs of the hood protector behind the rubber seal, lining up the holes in the mounting tabs with the holes in the hood. Using the screws with flat washers, attach the hood protector to the hood. Tighten just enough to hold the hood protector in place.
- 4 Close the hood **CAREFULLY** to check the fit. If the hood protector is not centered, slightly loosen the screws and move it to one side or the other until it is centered. When you are satisfied the hood protector is in place, tighten the screws until snug. **DO NOT OVER TIGHTEN this may damage your new hood protector.**

CLEANING: USE ONLY SOAPY WATER AND A SOFT CLOTH. NEVER USE PAPER TOWELS, PETROLEUM PRODUCTS OR SOLVENTS TO CLEAN YOUR HOOD PROTECTOR.

Stampede Automotive Products • Visit us at stampedeproducts.com • 800-241-7219

KIT CONTAINS:
HOOD PROTECTOR
6 WASHERS
6 SCREWS
TOOLS NEEDED:
PHILLIPS
SCREWDRIVER