

2013 FORD MUSTANG GT

Sport Grille

Install time: 30 Mins.

TOOLS REQUIRED:

Screwdriver
Socketwrench
Flat Screwdriver

PARTS LIST:

(3) Mesh Grilles	(2) 6/32 Nylon Lock Nuts
(3) 2.5" 6/32 M-Screws	(1) Spring Wing Clip
(1) #8 2" 6head Screw	(2) J-Hooks (polished)
(2) L-Brackets	(2) Fender Flatwashers

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS
BEFORE ATTEMPTING INSTALLATION.

Step 1 Factory Removal

- Remove 7 Pop Clips from the Plastic Cover. (Fig. 1)
- Remove Plastic Cover
- Insert the U-Nut through the Flange Bracket (Have the wider hole on the U-Nut face towards you). (Fig. 2)

Step 2 Grille Installation

- Remove the Center Pony Logo.
- Place the Center Mesh Grille onto the Factory Grille.
- Insert M-Screws through the Brackets with the holes that are on the Mesh Grille.
- Place the J-Hooks through the Center of the Grille.
- From Behind the Mesh Grille, Place an L-Bracket through the M-Screw and Thread in with the Nylon Lock Nut.
- Place Fender Flatwashers through the J-Hooks and Thread the Nylon Lock Nuts. Repeat for Remaining Screws.
- Get the Right side of the Mesh Grille and Place an M-Screw onto the Bracket with the hole and Thread the Wing Clip many times so it wont be loose. (Fig. 2)
- Place Grille onto the Factory Opening and Thread the Screw. (Apply some pressure so the Wing Clip wont move around when Threading).
- With a 1/8 Drillbit, get the Left side of the Mesh Grille and place it onto the Factory Grille. Drill Through the Bracket that has the hole and Thread the 6Head Screw in.

INSTALLATION COMPLETE

