



Installation Instructions

Tow Hook

p/n's 13200, 13230

As you read these instructions, you will see **NOTES**, **CAUTIONS** and **WARNINGS**. Each message has a specific purpose. **NOTES** are additional information to help you complete a procedure. **CAUTIONS** are safety messages that indicate a potentially hazardous situation which, if not avoided, may result in minor or moderate injury. A **CAUTION** may also be used to alert against unsafe practice. **WARNINGS** are safety messages that indicate a potentially hazardous situation, which, if not avoided could result in serious injury. **CAUTIONS** and **WARNINGS** identify the hazard, indicate how to avoid the hazard, and advise of the probable consequence of not avoiding the hazard. **PLEASE WORK SAFELY!**

WARNING

To Prevent Serious Injury :

- | Keep all persons safely away from both vehicles and connecting rigging
- | Do not exceed the rating of the rigging being used
- | The anchor point on the other vehicle must be capable withstanding stress beyond the pull
- | If the attaching point were to break when using these items, they could recoil with immense force
- | Weak anchor points can break, possibly causing property damage or physical injury due to the recoil of the attaching system

1. Pick a desirable location to attach the Warn Tow Hook. This location may be on the vehicle frame, front or rear bumper, Warn Winch Mounting Bracket, etc. (**NOTE:** Some competitive winch mounting kits may not have sufficient strength to support heavy loads).

CAUTION: To prevent personal injury or vehicle damage, the location you choose must be capable of supporting at least 10,000 pounds of force.

2. When you have chosen the location for the Warn Tow Hook, place it in the desired position and mark the two holes for drilling.
3. Drill two 9/16" (.5625) dia. or 14mm dia. holes at the places marked.
4. Align the holes in the Tow Hook with the drilled holes and insert the two 1/2-13 x 2 " hex cap screws. Secure with lockwashers and hex nuts.

CAUTION: If for any reason you replace the capscrews with longer or shorter ones, they must be 1/2-13, grade 5 or 8. **DO NOT USE STANDARD GRADE 2 CAPSCREWS.**

5. Tighten capscrews to 75 lb./ft., 10.3kg./m.
6. Your Tow Hook is now ready for use when you need it. Thank you for purchasing it from Warn Industries.



WARN® ATV/ UTILITY/ MOUNTING SYSTEM/ ACCESSORY PRODUCTS

LIMITED ONE (1) YEAR WARRANTY STATEMENT

Warn Industries, Inc. (WARN) warrants to the original purchaser that the mechanical components and electrical components of the "WARN" Products specified below will be free of defects in material and workmanship for a period of one (1) year from the original date of purchase. This Warranty applies only to the original purchaser of the Products. To obtain any warranty service, you must provide WARN with proof of purchase and date of purchase acceptable to WARN, such as a copy of your purchase receipt. This warranty does not cover the removal or reinstallation of the Product. WARN will, at its option, repair, replace or refund the purchase price of a defective Product or component, provided you return the defective Product or component during the warranty period, transportation charges prepaid, to Warn Industries' Service Department or a Factory Authorized Service Center. Attach your name, address, telephone number, a description of the problem, and a copy of your receipt and original bill of sale bearing the WARN serial number of the defective Product and date of purchase.

This warranty does not apply (i) to parts or components excluded below, or (ii) if the Product has been damaged by accident, abuse, misuse, collision, overloading, modification, misapplication, improper installation, or improper service. This warranty is void if any WARN serial number has been removed or defaced. Commercial or industrial use or application, or any hoisting application of the Product voids the warranty.

THE WARRANTY SET FORTH ABOVE IS THE ONLY WARRANTY. THERE ARE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ANY IMPLIED WARRANTY WHICH BY LAW MAY NOT BE EXCLUDED IS LIMITED IN DURATION TO ONE (1) YEAR FROM THE DATE OF ORIGINAL RETAIL PURCHASE OF THE PRODUCT.

WARN SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LOST PROFITS, DOWN TIME OR LOSS OF USE) UNDER ANY LEGAL THEORY, EVEN IF WARN WAS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Some states do not allow the exclusion of implied warranties or the exclusion or limitation of liability for incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights that vary from state to state.

WARN reserves the right to change Product design without notice. In situations in which WARN has changed a Product design, WARN shall have no obligation to upgrade or otherwise modify previously manufactured Products.

No WARN dealer, agent or employee is authorized to make any modification, extension or addition to this warranty.

Warranty inquires and Products returned for warranty service should be sent to:

WARN INDUSTRIES, INC
Customer Service Department
12900 SE Capps Road
Clackamas, OR 97015
1-800-543-WARN (1-800-543-9276)
1-503-722-3005 International Fax

Products covered by this Warranty

ATV Winch Products
Utility Winch Products
Winch Mounting Systems, Bumpers, Body Armor
ATV Mounting Systems & Bumpers
ATV Disconnect
All Accessories
ATV Plows, Lifts & Mounting Systems

Products Not Covered by this Warranty

Finish and Wire Rope for ATV Winch Products
Finish and Wire Rope for Utility Winch Products
Finish to Winch Mounting Systems, Bumpers & Body Armor
Finish to ATV Mounting Systems & Bumpers
Finish to ATV Disconnect
Finish to all accessories and Light Bulbs
Finish to ATV Plows & Mounting Systems
Synthetic Rope