



# INSTALLATION INSTRUCTIONS

## ATV WINCH MOUNT

Mount Kit: PN 36693, or 39319

Application: YAMAHA 600 GRIZZLY

Your safety, and the safety of others, is very important. To help you make informed decisions about safety, we have provided installation and operating instructions and other information on labels and in this guide. This information alerts you to potential hazards that could hurt you or others. It is not possible to warn you about all potential hazards associated with this product, you must use your own good judgment.

**CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.**

This guide identifies potential hazards and has important safety messages that help you and others avoid personal injury or death.

**WARNING** and **CAUTION** are signal words that identify the level of hazard. These signal words mean:

**WARNING** signals a hazard that could cause serious injury or death, if you do not follow recommendations.

**CAUTION** signals a hazard that may cause minor to moderate injury, if you do not follow recommendations.

This guide uses **NOTICE** to call attention to important mechanical information, and **Note**: to emphasize general information worthy of special attention.

## WARNING

**SEVERE INJURY OR DEATH MAY RESULT IF YOU IGNORE ANY OF THE FOLLOWING.**

- **Read the Winch Operator’s Manual, ATV Operator’s Manual, and all warning labels before operating the winch and ATV.**
- **Stay clear of moving parts and cable. Keep others away when operating the winch.**
- **Inspect the winch mechanism, fasteners, and cable, before operating. Replace all worn or damaged parts before operating.**
- **Make sure the winch is deactivated when leaving the ATV unattended.**

## PARTS LIST:

<u>PART NO.</u>	<u>QUANTITY</u>	<u>DESCRIPTION</u>
36649	1	Winch Mounting Plate
22508	2	8M x 1.25 x 25mm Hex Head Capscrew
1402	4	5/16 Lock Washer
2195	4	Spacer Washer
39324	2	8M x 1.25 x 20mm Button Head Capscrew

## INSTRUCTIONS:

1. Remove the four fasteners attaching the skid pan and remove the skid pan.
2. On the '98 model only, remove the bottom two fasteners that attach the radiator. This will allow the radiator to be moved out of position to allow the mounting plate to be slipped into place.
3. Remove the two lower rear fasteners that attach the front tube assembly to the frame.
4. Place the mounting plate into position. The flat side of the mounting plate will be facing up. The two long bent down tabs will line up with the two rear fasteners that were removed in step 3. There may be a space between the mounting plate and the tube, this space can be taken up with the spacer washers provided. Run the 8mm x 1.25 x 25mm capscrews with lock washer through the mounting plate, spacers (if needed) and into the tube on the bike. Only tighten finger tight at this time.
5. On the '98 models, replace the two fasteners that attach the bottom of the radiator and tighten securely.
6. Place the winch into position with the drum rotation label facing forward. Fasten with the four 5/16-18 x 1 1/2 capscrews and lockwashers provided with the winch. Tighten securely at this time.
7. Place the skid pan back into position. The skid pan should fit behind the front two tabs on the mounting plate. Replace the four fasteners that were removed in step 1. The top two fasteners will be replaced with the 8M x 1.25 x 20mm button head cap screws and lock washers, attach through the mounting plate and into the skid pan. Tighten all fasteners securely at this time.
8. Make the electrical connections using the winch manual provided with the winch. Refer to instruction PN 65094 for motor rotation instructions if installing a 3.0ci winch.



