



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**



### INSTRUCTIONS FOR P/N 7037/7038

The supplied crankshaft bolt and washer is used to fasten the pilot for the two-groove pulley (7036) and the harmonic dampener to the crankshaft. Torque to 60 ft./lbs. for small blocks or 80 ft./lbs. for big blocks. It is recommended to use Loctite or equivalent adhesive on the bolt threads.

**W517**